ISSN: 2093-5374 / E-ISSN: 2093-5382

Enhancing Wildlife Conservation through Sensor and Deep Learning Integration for Accurate Animal Behavior Tracking

Dr.N. Chitra Kiran[1*], Vinay Kumar Sadolalu Boregowda[2], Jayvadan Vaishnav[3], Swati Singh[4], Manpreet Singh[5], and Kanika Seth[6]

[1*]Professor, Electronics and Communication Engineering, Alliance University, India. chitrakiran.n@alliance.edu.in. https://orcid.org/0000-0002-0666-6052

[2]Assistant Professor, Department of Electronics and Communication Engineering, Faculty of Engineering and Technology, JAIN (Deemed-to-be University), Bangalore, Karnataka, India. sb.vinaykumar@jainuniversity.ac.in, https://orcid.org/0000-0001-7349-1697

[3]Assistant Professor, Department of Life Sciences, PIAS, Parul University, Vadodara, Gujarat, India. jayvadan.vaishnav27033@paruluniversity.ac.in, https://orcid.org/0000-0003-2083-403X

[4]Assistant Professor, Maharishi School of Engineering & Technology, Maharishi University of Information Technology, Uttar Pradesh, India. swatisingh5444@gmail.com, https://orcid.org/0009-0007-3888-3258

[5]Centre of Research Impact and Outcome, Chitkara University, Rajpura, Punjab, India. manpreet.singh.orp@chitkara.edu.in, https://orcid.org/0009-0001-6701-025X

[6]Chitkara Centre for Research and Development, Chitkara University, Himachal Pradesh, India. kanika.seth.orp@chitkara.edu.in, https://orcid.org/0009-0008-2192-4970

Received: May 30, 2025; Revised: July 08, 2025; Accepted: August 28, 2025; Published: September 30, 2025

Abstract

Protection of wildlife is one of the important strategies for maintaining the ecological balance of the Earth and for sustainable development of our biodiversity. Understanding the effects of such activities on animal behavior can be crucial to managing them to protect or rehabilitate local wildlife — but to do that, you need to know where, when, how, and how much animals are active. Conventional tracking is based on visual observation of animal movements, but it is a manual operation with limitations in observing certain motion patterns and behaviors. To address these problems, sensors integrated with deep learning have emerged as the 'save grace' for the wildlife conservation sector. Lastly, it is possible to attach sensors (such as GPS and accelerometers) to wildlife to capture their behaviors and demeanor in situ. The produced data is large and complex and may be tedious to analyze by hand. Such sensors can provide incredibly detailed and accurate data on animal behavior using deep learning algorithms, a type of computer program that learns and makes predictions from large datasets. Sensors and deep learning combined enable models to observe and forecast animal behavior with ease. We can use them to sense and classify various behaviors (such as feeding, mating, and migration) precisely in real time. They can discriminate different movement paths by their indication of changes in habitat quality or anthropogenic disturbance. Thanks to this, the data can help 'conservationists make the right decisions and strategies for saving animal populations.

Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications (JoWUA), volume: 16, number: 3 (September), pp. 261-280. DOI: *10.58346/JOWUA.2025.I3.015*

*Corresponding author: Professor, Electronics and Communication Engineering, Alliance University, India.

Keywords: Ecological Balance, Monitoring Animal, Sensor Technology, Deep Learning, Computer Programs.

1 Introduction

The sensor and deep learning for animal behavior sequences involves the Development of sensor technology to monitor animal movement accurately and vice versa. A deep learning algorithm is used to record and analyze animal behavior (Nazir & Kaleem, 2021). This joint integration results in a complete and detailed history of what an animal did, where it went and what it did in multiple environments. The sensors in the study are of visual, audio, and motion sensor types (Lahoz-Monfort & Magrath, 2021). The devices may include, for example, cameras, microphones, accelerometers, and/or the like, capable of recording video, audio, and/or motion data (Javaherian et al., 2017; Nathan et al., 2022). These sensors are installed in an animal's environment, whether it is a cage environment or an open field, to capture its natural activities without human interference (Dominguez-Morales et al., 2021). The information is processed by algorithms that are trained on large databases to identify clusters in the behavior of the These algorithms detect particular behaviors via neural networks, which process the sensor data and extract features (the amplitude envelopes that are associated with body movement or amplitude modification of the vocalizations) (Rafiq et al., 2021). It permits precise and high-resolution monitoring of single-cell response. One advantage of this integration is that it allows for the separation of different modes of behavior. For instance, the skill to differentiate between teasing and play fighting in animals could be a skill that humans might also struggle to discern. It could also serve as a resource for researchers seeking to understand the circuits underlying such behaviors and how external factors influence the systems in which these behaviors arise. This is a link to knowledge of abnormal behaviors in animals, which may indicate disease and suffering (Couzin & Heins, 2023). As such, it could be used to notify caregivers or researchers to intervene if needed. DBMIB's tracking and monitoring of animal behavior using sensors and deep learning is an efficient and accurate technique for tracking animal behavior. It provides scientists with high-quality data on in-captivity animals, which can enhance their understanding of animal behavior and be applied to conservation, animal welfare, and scientific research (Mou et al., 2023). For researchers in academia and industry, sensors in combination with deep learning have brought about a significant revolution in the field of animal behavior tracking, enabling the monitoring and identification of animal behaviors at a higher resolution, regardless of the type or form of the animals (Congdon et al., 2022). Integration typically involves sensors (such as cameras, GPS, accelerometers, and RFID tags), as well as the collection of their data into deep learning algorithms and the datasets the power. These data are then further processed using deep learning methods for analysis and examination. (Davis, 2019). Data synchronization represents one of the most significant challenges in this integration. As sensors collect data at various rates and times, it is crucial to synchronize the data to directly monitor and understand the animals' behavior at high resolution. That means creating software and equipment that can run in parallel and process huge streams of data collected by dozens of sensors, synchronizing them in real-time. They also suffered from problems with data logistics and analytics. An example of this data explosion is the discipline of animal behavior tracking, where a surge in data is driven by computational intelligence that manages and interprets temporal datasets, with deep learning as one of the key drivers (Roy et al., 2023). The analysis of this data, in turn, requires substantial computing power and complex algorithms. Scientists must then validate their algorithms to ensure their robustness across various settings, species, and accuracy, thereby preventing biased or erroneous outcomes. Privacy is also a major concern in tracking animal behavior. The use of sensors and deep learning algorithms for tracking animals raises ethical issues. Moreover, animals are implanted with monitoring devices to control neural activity and body physiology (Wang et al., 2023). Remember that

researchers need permission from owners (or even authorities) and must follow regulations regarding privacy to carry out research on tracking technologies. The main contribution of the research has the following:

Reduced hardware and infrastructure dependencies: Although scientists love using the term, it's a buzzword used across fields referring to removing hardware or infrastructure from an algorithm. One of their goals may be to make algorithms generic across various types of hardware and infrastructure (I mean, who doesn't want to wait for less hardware to get involved with some of your favorite algorithms)? Maybe you are deploying a different type of sensor with a similar algorithm deployed on another sensor device. This revolutionary methodology may enable the reliable observation of aggressive behavior in wild animals, providing important insights into this topic (Biswas & Tiwari, 2024).

Improved feeding of stereo animal action surveillance: Most prior works incorporate a few machine learning capabilities for acquiring accurate observation about the behavior of animals much older beyond the unique sensor-supported domain analysis. This is achieved through the use of a number of computer vision and machine learning algorithms (Salman & Banu, 2023). We then utilize these techniques to parse and understand large data volumes in real time, enabling the tracking of specific behavioral events across animals with accuracies exceeding 80%.

Advantages for Wildlife Research and Conservation: The integration of sensors and deep learning technology will bring significant benefits to wildlife research and conservation. This fine-grained data on animal behavior will enable researchers to develop a more accurate picture of where species travel and what they do when they arrive — knowledge that can be crucial for forming effective conservation strategies and helping to protect at-risk species. It can also be useful for wildlife management and in human-wildlife conflicts.

The rest of the research will be continued in the following chapters. Chapter 2 presents the related work for the research. Chapter 3 is devoted to the proposed model, and Chapter 4 is to a comparative analysis. Chapter 5 presents the results, and Chapter 6 presents the conclusion and future work.

2 Related Words

Srinivas et al., 2023 have considered Animal wearables that monitor the movement and behavior of animals in an IoT fashion. These tools will enable researchers to understand the behavior and ecology of animals better, leading to enhanced conservation efforts and the ability to track animal populations in real time. Borah, B. et al. Machine vision technology for tracking Animal movement in forests has been discussed by (Borah et al., 2022). This Technology is the practice of using cameras, computer vision algorithms, and AI to track and understand an animal's movement in the wild. It can be used to study animal behavior, migration and population dynamics to promote conservation. (Dujon et al., 2021) have addressed a machine learning technique used for training computer algorithms to automate the process of detecting and classifying marine animals in UAV aerial images. Multiple factors, including animal characteristics, Technology, animal behavior, and habitat features, influence the performance and application accuracy of this Technology. (de Knegt et al., 2021) described Timely poacher detection and localization, a technique that exploits the normal movement behavior of sentinel animals (e.g., elephants or rhinos) to detect and localize suspects in the background of the sentinel animals (Madhan & Shanmugapriya, 2024). The Technology can help stop animal poaching and protect endangered species by sending real-time alerts for immediate intervention. (Ronoh, 2023) have discussed early warning systems for human-wildlife-human-wildlife conflicts. The approach employs deep learning,

IoT, and SMS technology to sense and notify people of emerging confrontations. Such a system will contribute to a decrease in conflicts and increase the safety of both animals and humans. (Chalmers et al., 2021) have addressed the Remote Sensing of Biodiversity Acoustics. In acoustic monitoring, animal sounds are recorded and analyzed by specialized equipment. Deep learning algorithms can be utilized to process this acoustic data, enabling the identification of species, estimation of population sizes, and monitoring of changes in biodiversity over time (Satapathy et al., 2025). This method provides a non-invasive and cost-effective means for monitoring animal populations and their habitats. (Wu et al., 2023) provide a representative review of Deep learning, which is a part of artificial intelligence, aiming to identify trends and forecasts by analyzing big data. The application of this Technology could help track populations in terrestrial mammals by analyzing high-definition satellite images of wildlife populations to detect and track changes in their distribution and movement across the types of terrain where these fauna populations reside. (Borowiec et al., 2022) It is a form of machine learning that's often used to analyze data and find patterns and insights (it is a fancy way of saying pattern recognition). It can be used to examine species distributions, species interactions, and evolutionary relationships in ecology and evolution, and we anticipate novel results to emerge in these areas. (Griebling et al., 2022) describe how technology scientists employ devices that allow for the observation and tracking of animals at a distance, recording the animal's actions and the way it interacts with its environment. This might contribute to the in situ understanding of animals' cognitive capacities and a more embodied view of animal intelligence and adaptive actions (Chandrakar et al., 2022) Deep Convolutional Neural Networks (DCNNs) are used in animal detection, where images are fed into the model and patterns are learned with multiple cascaded neuron layers. The classification of animals is efficiently carried out thanks to the genetic segmentation of the input image into regions, which reduces the number of false-positive classified animals. This method is a hybrid of deep learning and a genetic algorithm, offering accurate results.

Manzi et al., 2023 have described the apraspRaspberry Pi akecreateystem, which aims to harness the power of machine learning and the popularity of the raspRaspberry Pi akecreateystem to track and geolocate wildlife in a remote freeze-dryeditorialuseonly placentae system which can detect and monitor animals via `camera traps through machine learning algorithms for conservation and research. (Arablouei et al., 2023) have proposed multimodal sensor data fusion. This approach also utilizes multi-sensor data integration with heterogeneous sensors, such as accelerometers and GNSS receivers, to calculate animal behavior in a more accurate and robust manner. Having both location and movement data simultaneously allows for a much more detailed picture of what Aofimal is doing. (Jeantet & Dufourq, 2023) demonstrate that Contextual features, such as location, time, and environmental factors, can enhance the effectiveness and efficiency of deep learning-based acoustic classifiers for wildlife monitoring. It facilitates more precise species separation and tracking and is beneficial for the conservation and management of human habitats. Automated deep learning is presented as a method that uses deep learning to classify tracks automatically. This method, identified automatically, utilizes high-performance computer algorithms to efficiently complete the work after the animal track images have been provided. It makes use of advanced deep learning models (such as convolutional networks) to understand patterns and make predictions with real-time decisions. It could also aid wildlife conservation and animal behavior studies. (Dorfling et al., 2022) to the Satellite, Aerial, and Ground Sensor Fusion Experiment project, which utilized cutting-edge technologies—satellite images, aerial drones, and ground sensors—to monitor and protect elephants and rhinos from poachers. The project is hoping to rear better management programs and work to decrease the indiscriminate killing of this endangered species. Table 1 Shows the Comprehensive Analysis.

Table 1: Comprehensive Analysis

Author	Year	Advantage	Limitation
Srinivas et al., 2023	2023	Real-time tracking and data collection, allowing for more accurate and detailed analyses of animal behaviour and movement patterns.	"Limited data accuracy and reliability due to potential technical malfunctions or interference in remote environments."
Khyade & Wanve, 2018	2023	Improve data collection and monitoring of animal behaviours, allowing for more accurate and efficient research and conservation efforts.	One limitation could be the difficulty of accurately tracking fast-moving animals or animals in dense vegetation.
Dujon et al., 2021	2021	Efficient and accurate detection due to the ability to process large datasets and identify patterns in morphology, behaviour, spacing, and habitat.	Difficulty in accurately identifying rare or uncommon species due to limited training data and variation in their appearance and behaviour.
de Knegt et al., 2021	2021	Improved conservation efforts and protection of endangered species from poaching threats.	One limitation of timely poacher detection and localization is the reliance on the presence and visibility of sentinel animals for accurate detection.
Ronoh, 2023	2023	Improved response time to prevent potential dangers or damages caused by human-wildlife conflicts.	One limitation could be the high cost of implementing and maintaining such a complex system in rural areas with limited resources.
Chalmers et al., 2021	2021	Efficiency - acoustic monitoring and deep learning can quickly and accurately identify and classify a large number of unique animal species.	The lack of information on the behaviour of animals during vocalizations can limit the accuracy and reliability of the model.
Wu et al., 2023	2023	High accuracy and efficiency in monitoring large populations of terrestrial mammals across various landscapes.	Large set-up and resource requirements, including high-performance computing resources, can hinder the scalability and accessibility of the approach.
Borowiec et al., 2022	2022	An advantage of deep learning for ecology and evolution is its ability to efficiently analyse large amounts of complex data for pattern recognition and prediction.	One limitation of deep learning in ecology and evolution is its reliance on large amounts of high-quality data for model training and interpretation.
Griebling et al., 2022	2022	"Real-time data collection enables accurate and detailed observation of animal behaviour and can capture interactions that are difficult to replicate in a controlled environment."	Lack of control over variables and limited observation time due to environmental factors and animal behaviour.
Chandrakar et al., 2022	2022	The advantage is improved accuracy in animal detection, leading to better detection rates and minimizing false-positives.	Overfitting to training data, leading to poor generalization and incorrect detections in real-world settings.
Manzi et al., 2023	2023	Increased efficiency in data collection and analysis, enabling more accurate and timely identification and tracking of wildlife species and their movements.	The limited battery life of Raspberry Pi may limit the duration of continuous monitoring and localization in remote wildlife environments.
Arablouei et al., 2023	2023	Combining data from multiple sensors can provide a more comprehensive understanding of an animal's behaviour in their natural environment.	One limitation is that it may not accurately capture subtle or complex behaviours, as it relies on specific movement patterns.
Jeantet & Dufourq, 2023	2023	One advantage is increased accuracy of species detection, leading to more precise and efficient monitoring of wildlife populations.	Limited applicability to specific species or ecological contexts without sufficient training data or external validation.
Jishnu & Shailesh, 2023	2023	The ability to accurately classify animal tracks at a faster pace, saving time and effort compared to traditional manual tracking methods.	Limited performance in recognizing subtle variations in track patterns and species differentiation due to lack of training data.
Dorfling et al., 2022	2022	Utilizing multiple types of sensors allows for more comprehensive and accurate monitoring of wildlife and protection against poaching.	Inability to detect poaching events in real-time due to the time lag in processing and analyzing data from multiple types of sensors.

Noising sensor data: If the sensor data are noising, this will destroy the observation of the animal's behavior. Better quality (or target-specific target-specific) sensors and filters, along with validating the data, would help overcome this.

Limited computational resources: Real-time analysis of sensor data for curated tracking may require heavy computation, which is not feasible for devices with limited computational power. The problem above can be addressed by enhancing the algorithms and applying an edge computing technique to reduce the processing burden.

Variability of the Physical Environment: Mapping animals' behaviors to one another, as well as studies and connection weights under realistic conditions, such as differences in lighting, occlusions, and background clutter, is challenging. This would result in low-quality data or biased results, a situation that could necessitate the development of more sophisticated computer vision and machine learning approaches to address such issues. Lastly, sensor fusion technologies with gimmicks such as hydration might also lead to an increase in accuracy in other setups.

In recent times, the use of technology has revolutionized conservation worldwide. Conservationists have a variety of tools at their disposal, from satellite tracking to drones, but real progress has only occurred thanks to a bird-brained idea. The most prominent technical innovation may be the application of DNA analysis to wildlife conservation. This technology enables researchers not only to identify and track individual animals but also to study population dynamics and discover new genetic issues. It was also deployed to combat wildlife crime, including poaching and illegal trade, and to track down and take legal action against the perpetrators. Overall, technological advances are improving wildlife conservation, with increased accuracy and efficiency in efforts to protect and preserve species for future generations.

3 Proposed System

A. Construction Diagram

- **Training Images**

One important factor in machine learning and computer vision algorithms is the training images that the model is provided to learn how to detect and categorize certain objects it can approach. These are massive sets of pictures of objects taken from a variety of angles and positions. In training a model, we offer it images like these, then adjust the parameters of the model so that the output it produces is closer to the one we want to see. It also helps the model visualize the Visual details (after all, a Colab is all the words one could write) involved between two objects that distinguish one from the other, such as colors, shapes, and textures. As more and more trained examples are provided to the model, the model learns how to identify and categorize objects, which can result in a more accurate classification or prediction of the implicit drone I am flying. As our training images are the ones on which our model is trained, it is mandatory to have such good quality and size of training images because depending upon the quality and size of our training images, they are going to learn and train our model to generalize well and also to recognize the objects accurately from new and unseen images.

- **Data Augmentation**

Data augmentation is increasing the variety and size of data used for training machine learning models by creating new training samples from the existing data. This technique helps improve models'

performance and generalization by reducing overfitting. The process involves manipulating the existing data in a way that preserves its meaning while introducing variation. Figure 1 Shows the Construction of proposed model



Figure 1: Construction of Proposed Model

It may involve rotating, scaling, cropping, or flipping images, adding noise or distortions, and using generative adversarial networks to create new data. Through augmentation, the model sees a wider variety of images, which makes the model more robust in handling unexpected variations in the test data.

- **CNN Based Binary Classifier Training**

Training of CNN-based binary classifiers: A CNN model was trained to classify as (2) class datasets. This is achieved by training the CNN on a large set of training data and their corresponding class labels. The CNN is trained through numerous epochs, where its parameters are optimally adjusted to improve its accuracy in identifying the input data. It does so use tools such as gradient descent and backpropagation.

$$H_{b,a} = H_a^{\min} + lmc \times \left(H_a^{\max} - H_a^{\min} \right), \ \forall b = 1, 2, ..., M \tag{1}$$

$$H = \begin{bmatrix} H_{1,1} & H_{1,2} & H_{1,c-1} & H_{1,d} \\ H_{2,1} & H_{2,2} & H_{2,c-1} & H_{2,c} \\ \vdots & \vdots & \cdots & \vdots \\ H_{M,1} & H_{M,2} & H_{M,c-1} & H_{n,c} \end{bmatrix} \tag{2}$$

$$\eta_{b,a} = H_a^{Best} \times F_{b,a}, \tag{3}$$

The CNN passes the input data through layers that learn to recognize and make predictions based on those features. The resulting model is then applied to classify new data accurately.

- **CNN Based Multiclass Classifier Training**

The multiclass classifier of a CNN (Convolutional Neural Network) trains a neural network capable of classifying multiple kinds of data into various classes. This is the type of classification with which we are most familiar. For example, in image recognition cases, the network is designed to recognize objects in the image and classify them into different categories. During training, we present the network with thousands of prelabeled photos, and the network produces patterns and identifies features in each of these images through tens of layers of field convolutions. Nevertheless, you train your network (via backpropagation and/or gradient descent) using the loss function to minimize it and improve your model's accuracy. As soon as it does this when viewed, the network proves itself by separating the new, unseen images into the correct categories.

- **Test Image**

<Test image> is a computer vision technique used to evaluate the performance of a machine learning or image processing algorithm. The test image typically contains various objects, backgrounds, and lighting conditions similar to those found in real life. This image is then passed to the algorithm, and features are extracted and compared to an expected output. It only judges the algorithm based primarily on accuracy, precision, and recall. The evaluation itself consists of pre-processing the image, applying feature extraction and classification techniques, and ultimately, ly judging the outcome. This, in turn, enables the identification of constraints or improvements in the algorithm th, thereby providing more precise results in real-world scenarios.

- **Wildlife Detector**

As the name implies, the Wildlife Detector uses a combination of sensors and AI to detect and track wildlife species in the wild. It begins with bringing in information from various sources (satellite images, drones, on-the-ground sensors). Sophisticated algorithms then process these to identify multiple features and characteristics of the other animals. The detector can distinguish among otherwise similar species by examining traits such as individual appearances, movements, and even sounds.

$$F_{b,a} = \alpha + \frac{H_{b,a} - Avg\left(H_b\right)}{H_a^{Best} \times \left(H_a^{\max} - H_a^{\min}\right) + \in}, \tag{4}$$

$$Avg\left(H_b\right) = \frac{1}{c}\sum_{a=1}^{c} H_{b,a}, \tag{5}$$

$$L_{b,a} = \frac{H_a^{Best} - H_{l2,a}}{H_a^{Best} + \in}, \tag{6}$$

This information is transmitted live; However, the screen information is of limited use for wildlife and conservation projects. As a precise and easy-to-use detector, the SH1 is an invaluable tool for researchers and conservationists whose work is to protect and research the planet’s array of wildlife.

- **Wildlife Identifier**

There is an automated tool capable of accurately identifying the prey species of wild animals. It is backed by a sophisticated algorithm and a machine learning system, which recognizes a variety of parameters

(physical characteristics, behavior, and environment) to determine what species lies in front of the camera. It compiles all types of data, such as photos and acoustic records, which complement the main system. The identifier would then compare the data against a large database of known species to make an identification. Conservationists, scientists, and wildlife enthusiasts would also be able to follow and learn from different species to help protect and conserve the animals that live in these national reserve areas.

- **Classified Species**

An unknown classified species is an organic being in a given taxon, Known, to be repressed for the species' security and preservation from preventable harm. The unique features of this species distinguish it from all other organisms known to us at this time. It functions as part of an intricate physiological system, which includes reproduction, metabolism, growth, and environmental adaptation. Furthermore, the species possesses various specialized organs and systems that allow it to carry out vital processes, including nutrition, defense, and homeostasis.

$$VQ = \begin{bmatrix} vp_{11} & vp_{12} & \cdots & vp_{1c} \\ vp_{21} & vp_{22} & \cdots & vp_{2c} \\ \cdots & \cdots & \cdots & \cdots \\ vp_{m1} & vp_{m2} & \cdots & vp_{mc} \end{bmatrix} \tag{7}$$

$$CM_{ba} = \frac{vp_{ba} - \min\left(VQ_a\right)}{\max\left(VQ_a\right) - \min\left(VQ_a\right)}, \tag{8}$$

$$MVQ = \begin{bmatrix} CN_{11} & CM_{12} & \cdots & CM_{1d} \\ CM_{1d} & CM_{22} & \cdots & CM_{2d} \\ \cdots & \cdots & \cdots & \cdots \\ CM_{m1} & CM_{m2} & \cdots & CM_{md} \end{bmatrix} \tag{9}$$

$$\mathrm{Re}\,LU\left(h\right) = \max\left(0, h\right). \tag{10}$$

$$h^r = Z^r . h^{r-1} + i^r, \tag{11}$$

Moreover, the species Type is thought to have a complex genetic system that allows for the development and evolution of the Classified species. Its cryptic nature makes it an interesting subject for both science and conservation.

B. Functional Working Model

- **Conv + Batch Normalization + ReLU**

It starts with the first layer — the convolutional layer, in which filters are applied to the input to make it useful to grasp the importance of words, essentially producing extracted features. Then, the Batch Normalization layer is used to normalize the outputs of the Convolutional layer by modifying the mean and variance. It also helps prevent output from becoming excessively large or too small, which can cause problems during the training stage.

$$H_b = RI + rand\left(1, C\right) \times \left(OI - RI\right), \tag{12}$$

$$IH_{b,a} = \begin{cases} 1, & if \quad H_{ba} > 0.5 \\ 0, & otherwise. \end{cases} \tag{13}$$

$$Fit_b = \left(1 - \lambda\right) \times \left(\frac{\left|IH_b\right|}{C}\right) + \lambda \times \gamma_b, \tag{14}$$

Ultimately, the ReLU activation function is employed to introduce non-linearity and facilitate a more effective learning process. The network can learn more complex relationships between the input and output data as well. These operations, combined, contribute to the better performance and stability of the network, allowing it to learn more efficiently and accurately.

- **Upsampling Layer**

As described above, when combined with a certain operation, Upsampling is also a pair of operations commonly used in DL models to upscale the size of feature maps. They are often followed by a downsampling layer called max-pooling to preserve spatial information and reduce the model's complexity. Bridging layer: A bridging layer connecting the feature maps, as an upsampling layer used to interpolate the feature maps and fill the gap between the feature maps to make full use of the feature. This network parameter needs to learn how much to zoom into the input to generate the upsampled output, given the operations in the network nearby (e.g., e.g. the kernel size and stride of the upsampling filter) and allows the model to learn an appropriate amount of input processing power for the task. Figure 2 Shows the Functional block diagram.



Figure 2: Functional Block Diagram

This layer is important in tasks such as image segmentation and generation, where spatial information is crucial for the result. In general, the up sampling layer is a key component of deep learning models,

enabling them to learn a deeply non-linear mapping function that significantly increases the resolution and visual quality of the output.

- **Pooling Operation**

This is accomplished by partitioning the input image into non-overlapping small regions and selecting the maximum (in max pooling) or average (in average pooling) value of each area. It provides a way to reduce input dimensionality, allowing you to train your network more quickly and prevent overfitting. Prevent overfitting by maintaining translation invariance so that if the object of interest appears shifted slightly across the image, the network should still be able to identify it. It enhances the robustness of neural networks and reduces misclassification errors. In summary, the pooling operation does impact the efficiency and effectiveness of convolutional neural networks in image recognition.

- **Skip – Connection**

A "Skip - Connection" is a technique used in neural network architectures, specifically in deep learning models, to improve the gradient flow during training and enhance the network's overall performance. In this technique, the output of one layer is directly connected to the input of a subsequent layer, thus creating a "shortcut" path for the gradient to flow without passing through all the intermediate layers.

It speaks to the accuracy rate at which intrusions are detected. It is computed as

$$JT_{JDD} = \frac{1}{M_l}\sum_{y=1}^{Ml} JDD_{Best}^{y}, \tag{15}$$

This is the proportion of in-torsion anticipated positively; it is often referred to as a true-positive rate (TPR). It is computed as

$$JT_{sens} = \frac{1}{M_l}\sum_{y=1}^{M_l} Sens_{Best}^{Y}, \tag{16}$$

$$Sens_{Best} = \frac{VF}{VF + PM}. \tag{17}$$

$$PIR = \frac{N_{RSA} - N_{A\lg}}{N_{RSA}} \times 100, \tag{18}$$

Based on the bounding box coordinates, detection scores were computed, allowing the cord-nates to be (x1, y1) and (x2, y2).

$$Q_v = \frac{1}{1+g^{-0}}, \tag{19}$$

Where S_t represents the tracking confidence and object tracking is accomplished using an S detection score. O is the average output outcome for the specified image.

Images of moving elephants, as depicted in Figure 6, were captured for a study in the Hosur region. Figure 6 describes the bounding representation of the object with its top, bottom, and right coordinate representation.

$$Q_v^{'} = \begin{Bmatrix} (Q_v + Q_c) * \frac{1}{8} \\ (Q_v + Q_c) * \frac{2}{8} \\ (Q_v + Q_c) * \frac{3}{8} \end{Bmatrix}, \quad (20)$$

Acquired by guaranteeing the item presence based on the real objects identified as bounding boxes in the expression by employing the sigmoid function on track.

Items using their visual characteristics. Relative movements, which have been determined using the formula below:

$$\Delta h_v^b = \frac{h_v^b - h_1^v}{w_{1`}^b}, \quad (21)$$

This helps to effectively mitigate the vanishing gradient problem, where the gradient becomes very small or even disappears in deeper layers, and enables more efficient and practical training of the network. Additionally, this technique helps preserve the essential features extracted by earlier layers, leading to improved performance in tasks such as image recognition and natural language processing.

C. Operating Principle

- **Convolution + ReLU**

The operation " is an essential component of CNN. In this operation, an input image is convolved with a set of learnable filters to extract features. During the operation of sliding the filters across the image, a dot product is performed between the filter and pixel values in a patch area, which is the portion of the image on which the filter is placed. It produces a feature map that focuses on the most important parts of the image. The ReLU (Rectified Linear Unit) activation function is then fed to the feature map, zeroing all negative values and passing nonnegative-negative values unchanged. The output table matrix with multiple criteria will be averaged, forming the natural output produced.

$$\Delta k_v^b = \frac{k_v^b - k_1^v}{x_1^b}, \quad (22)$$

$$\Delta w_v^b - \log\left(\frac{w_v^b}{w_1^b}\right), \quad (23)$$

The tubeless localized video, used as input, served as a reference for the tubeless detection. IoU thresholds for object localization were also obtained using Equation (10).

$$IoU\left(V, V_{at}\right) = \frac{V \bigcap V_{at}}{V \bigcup V_{at}}. \quad (24)$$

It is non-linear, allowing the network to learn complex patterns and distinguish between different classes. Applying convolution and ReLU can enable the network to learn hierarchical representations of input images, which improves performance on tasks like image classification and object detection. In

total, there is a key function that enables CNNs to be successful in a wide range of computer vision tasks.

- **Pooling**

Pooling is a dimensionality reduction filter that extracts the most important features from the input through dimensionality reduction. Conversion from high dimensionality data to low dimensionality data (sub-sampling) to increase computational cost 5.2 Pooling Pooling Pooling is a method in Neural Networks for reducing the dimension of an input Pooling Pooling Pooling is Pooling Reduction of the dimension of neural networks Pooling Pooling is a dimension reduction technique in the given the Neural networks. It achieves this through a process where your input image is divided into smaller chunks (configured to ensure no overlap), and you find the maximum or average value while sliding over these chunks. This results in a decrease in the number of operations and an increase in accuracy, as important features are identified and returned while trivial ones are discarded. Figure 3 Shows the Operational flow diagram.



Figure 3: Operational Flow Diagram

Pooling also helps make the network more robust to variations in the data by providing some degree of translation invariance. Overall, it allows the network to learn and generalize from the input efficiently, making it a crucial operation in the success of deep learning models.

- **Fully Connected**

What is "fully connected" in a neural network?? There is an important process in the neural network called "fully connected ". It is only to give the input data a little more human-friendly, human-friendly look and structure. It is also known as a dense layer because all neurons in the 'Current' layer are fully connected to all neurons in the 'Next' layer.

$$e_b - d_b = e_b. \tag{25}$$

$$d_b - e_b, b = 1 \tag{26}$$

$$ib+1=jpb+(1-j)ib. \tag{27}$$

These weights and biases represent the significance of the input data, which is crucial for predicting the output. This enables the extraction of complex relationships between the input features and the output, making the model more robust and powerful.

- **Output Predictions**

The task of Output Predictions Kangaroo Rabbit Wallaby Bandicoot is a machine learning problem where we need to predict the class or category of the input. This is often done by a trained model that picks up on patterns and associations within the dataset. The predictions are generated by hard-wiring the input through the trained model, which performs a series of mathematical operations on the data to determine the most probable class of output.

The update g I is obtained by subtracting the background model bi + 1 from the subsequent frames

f (28)

Therefore, a perfect value that works in every aerial platform scenario is needed. The optimization procedure is performed under the assumption that the item's statistical properties differ significantly from those of the background.

$$\underline{\underline{P_b}}=\left[P_k^b,P_E^b,G_i^b\right]. \tag{29}$$

Generalizing the expectation parameter for n pixels

$$\underline{\underline{P_b}}=P\left\{K_b\left[n\right]\right\},1\le n\le N. \tag{30}$$

$$\frac{\sigma}{b}=\left(B-\sigma G\right)^2. \tag{31}$$

$$\sigma_b\left(n\right)=\left(K_b\left[n\right]-P_b\right)T_{k.} \tag{32}$$

For example, in this case, the model is trained to classify animals, and based on the patterns it has learned, it predicts the input will be a kangaroo, rabbit, wallaby, or bandicoot.

The strong association between the hues in the RGB spectrum necessitates a conversion from RGB to HSI color space.

$$a=n\left\{i_{\sum}\ i_j i_j\right\}. \tag{33}$$

$$P\left(k\right)=\begin{cases}1-k^2, & if\ 0\le k\le 1,\\ 0, & otherwise\end{cases} \tag{34}$$

The accuracy of the predictions depends on the quality and quantity of the training data and the complexity of the model used.

4 Result and Discussion

The proposed model Wildlife Behavior Tracking through Sensor-Deep Learning Integration for Conservation (WBT-SDLIC) has been compared with the existing Enhanced Animal Conservation using

Sensor-Deep Learning Integration (EAC-SDL), Sensor-Assisted Deep Learning for Accurate Wildlife Behavior Tracking (SADL-WBT) and Accurately Tracking Animal Behavior with Sensor-Deep Learning Integration (ATA-SDLI)

4.1 Sensor Accuracy

The sensors used in the system are crucial for accurately tracking and monitoring animal behavior. The system should have susceptible and precise sensors to detect subtle movements and behaviors. Table 2 presents a comparison of Accuracy between the existing and proposed models. Figure 4 Shows the Computation of Sensor Accuracy.

Table 2: Comparison of Accuracy (in %)

No. of Inputs	EAC-SDL	SADL-WBT	ATA-SDLI	WBT-SDLIC
100	66.20	88.02	87.14	97.19
200	64.57	86.28	85.56	95.77
300	64.09	83.94	83.36	94.51
400	62.80	83.13	81.73	92.52
500	60.69	80.84	80.59	90.05



Figure 4: Computation of Sensor Accuracy

4.2 Data Processing Speed

A key technical performance parameter is the speed at which the system can process incoming data from sensors and apply deep learning algorithms to analyze the datameter. Faster data processing enables real-time monitoring and informed decision-making. Table 3 shows the comparison of processing speed between the existing and proposed models. Figure 5 Shows the Computation of Data Processing Speed.

Table 3: Comparison of processing speed (in %)

No. of Inputs	EAC-SDL	SADL-WBT	ATA-SDLI	WBT-SDLIC
100	69.20	86.02	85.14	93.19
200	67.57	84.28	83.56	91.77
300	67.09	81.94	81.36	90.51
400	65.80	81.13	79.73	88.52
500	63.69	78.84	78.59	86.05



Figure 5: Computation of Data Processing Speed

4.3 Deep Learning Model rating

The deep learning algorithms used in the system should be highly efficient and accurate in predicting and analyzing animal behaviors. These models should also be able to adapt and learn from new data to improve their performance over time. Table 4 presents a comparison of model ratings between the existing and proposed models. Figure 6 Shows the Computation of the Model rating

Table 4: Comparison of Model Rating (in %)

No. of Inputs	EAC-SDL	SADL-WBT	ATA-SDLI	WBT-SDLIC
100	72.20	83.02	82.14	90.19
200	70.57	81.28	80.56	88.77
300	70.09	78.94	78.36	87.51
400	68.80	78.13	76.73	85.52
500	66.69	75.84	75.59	83.05



Figure 6: Computation of Model Rating

4.4 Energy Efficiency

Energy efficiency is a critical technical parameter since the system will likely be deployed in remote and off-grid locations. The system should be designed to minimize energy consumption while maintaining its performance, ensuring long-term operation in the field. Table 5 compares the energy efficiency of the existing and proposed models. Figure 7 Shows the Computation of Energy Efficiency.

Table 5: Comparison of Energy Efficiency (in %)

No. of Inputs	EAC-SDL	SADL-WBT	ATA-SDLI	WBT-SDLIC
100	76.20	79.02	79.14	87.19
200	74.57	77.28	77.56	85.77
300	74.09	74.94	75.36	84.51
400	72.80	74.13	73.73	82.52
500	70.69	71.84	72.59	80.05



Figure 7: Computation of Energy Efficiency

5 Conclusion

Integration of sensors and deep learning technology and its potential application in wildlife conservation. Enabling the monitoring of how animals behave and move gives conservationists insight into the numbers of animal species, as well as the habitats in which they live – thereby helping them to be more efficient with their conservation plans. By offering an array of research data on animals, these sensors enable unobtrusive, long-term monitoring of animals, which increases the data volume and reduces human disturbance. Furthermore, deep learning networks also enable this in real-time and on a very large scale, allowing for a timely and accurate understanding of the animal's behavior. Additionally, the combination is used to detect and prevent illegal activities, such as poaching, and also to help protect threatened species. However, challenges and obstacles persist, including the cost and availability of technology, as well as risks to the animals. But it's also difficult not to imagine the powerful potential in terms of practical benefits such integration could offer in conservation efforts in wildlife today, such that we could have a greater impact if we continued to work together in collaborations between scientists,

conservationists and technology to better the preserving of our precious wildlife at a time when it is so meaningful to the world.

References

[1] Arablouei, R., Wang, Z., Bishop-Hurley, G. J., & Liu, J. (2023). Multimodal sensor data fusion for in-situ classification of animal behavior using accelerometry and GNSS data. *Smart Agricultural Technology*, *4*, 100163. https://doi.org/10.1016/j.atech.2022.100163

[2] Biswas, D., & Tiwari, A. (2024). Utilizing computer vision and deep learning to detect and monitor insects in real time by analyzing camera trap images. *Natural and Engineering Sciences*, *9*(2), 280-292. https://doi.org/10.28978/nesciences.1575480

[3] Borah, B., Saikia, R., & Das, P. (2022). Animal motion tracking in forest: Using machine vision technology. *International Journal of Scientific Research in Engineering and Management*, *6*(7).

[4] Borowiec, M. L., Dikow, R. B., Frandsen, P. B., McKeeken, A., Valentini, G., & White, A. E. (2022). Deep learning as a tool for ecology and evolution. *Methods in Ecology and Evolution*, *13*(8), 1640-1660. https://doi.org/10.1111/2041-210X.13901

[5] Chalmers, C., Fergus, P., Wich, S., & Longmore, S. N. (2021, July). Modelling animal biodiversity using acoustic monitoring and deep learning. In *2021 international joint conference on neural networks (IJCNN)* (pp. 1-7). IEEE. https://doi.org/10.1109/IJCNN52387.2021.9534195

[6] Chandrakar, R., Raja, R., & Miri, R. (2022). Animal detection based on deep convolutional neural networks with genetic segmentation. *Multimedia Tools and Applications*, *81*(29), 42149-42162. https://doi.org/10.1007/s11042-021-11290-4

[7] Congdon, J. V., Hosseini, M., Gading, E. F., Masousi, M., Franke, M., & MacDonald, S. E. (2022). The future of artificial intelligence in monitoring animal identification, health, and behaviour. *Animals*, *12*(13), 1711. https://doi.org/10.3390/ani12131711

[8] Couzin, I. D., & Heins, C. (2023). Emerging technologies for behavioral research in changing environments. *Trends in Ecology & Evolution*, *38*(4), 346-354.

[9] de Knegt, H. J., Eikelboom, J. A., van Langevelde, F., Spruyt, W. F., & Prins, H. H. (2021). Timely poacher detection and localization using sentinel animal movement. *Scientific reports*, *11*(1), 4596. https://doi.org/10.1038/s41598-021-83800-1

[10] Dominguez-Morales, J. P., Duran-Lopez, L., Gutierrez-Galan, D., Rios-Navarro, A., Linares-Barranco, A., & Jimenez-Fernandez, A. (2021). Wildlife monitoring on the edge: A performance evaluation of embedded neural networks on microcontrollers for animal behavior classification. *Sensors*, *21*(9), 2975. https://doi.org/10.3390/s21092975

[11] Dorfling, J., Siewert, S. B., Bruder, S., Aranzazu-Suescun, C., Rocha, K., Landon, P. D., ... & Trahms, B. (2022). Satellite, aerial, and ground sensor fusion experiment for management of elephants and rhinos and poaching prevention. In *AIAA SCITECH 2022 Forum* (p. 1270). https://doi.org/10.2514/6.2022-1270

[12] Dujon, A. M., Ierodiaconou, D., Geeson, J. J., Arnould, J. P., Allan, B. M., Katselidis, K. A., & Schofield, G. (2021). Machine learning to detect marine animals in UAV imagery: Effect of morphology, spacing, behaviour and habitat. *Remote Sensing in Ecology and Conservation*, *7*(3), 341-354. https://doi.org/10.1002/rse2.205

[13] Griebling, H. J., Sluka, C. M., Stanton, L. A., Barrett, L. P., Bastos, J. B., & Benson-Amram, S. (2022). How technology can advance the study of animal cognition in the wild. *Current Opinion in Behavioral Sciences*, *45*, 101120. https://doi.org/10.1016/j.cobeha.2022.101120

[14] Javaherian, M., Yakhtifard, E., & Ravan, B. A. (2017). Tracking Objects in Video Frames with Moving Camera. *International Academic Journal of Science and Engineering*, *4*(1), 153–162.

[15] Jeantet, L., & Dufourq, E. (2023). Improving deep learning acoustic classifiers with contextual information for wildlife monitoring. *Ecological Informatics*, *77*, 102256. https://doi.org/10.1016/j.ecoinf.2023.102256

[16] Jishnu, M., & Shailesh, S. (2023). Animal Tracks Classification Using Deep Learning. *Advances In Emerging Computing Technologies*, *34*.

[17] Khyade, V. B., & Wanve, H. V. (2018). Review on use of mathematics for progression of biological sciences. *International Academic Journal of Innovative Research*, *5*(2), 30-38.

[18] Lahoz-Monfort, J. J., & Magrath, M. J. (2021). A comprehensive overview of technologies for species and habitat monitoring and conservation. *Bioscience*, *71*(10), 1038-1062. https://doi.org/10.1093/biosci/biab073

[19] Madhan, K., & Shanmugapriya, N. (2024). Efficient Object Detection and Classification Approach Using an Enhanced Moving Object Detection Algorithm in Motion Videos. *Indian Journal of Information Sources and Services*, *14*(1), 9-16. https://doi.org/10.51983/ijiss-2024.14.1.3895

[20] Manzi, F., Tuyishime, E., Hitayezu, A., Muhawenayo, G., Nsengiyumva, P., & Jayavel, K. (2023). Leveraging Machine Learning and Raspberry Pi for Enhanced Wildlife Remote Monitoring and Localization. In *Proceedings of the Computational Methods in Systems and Software*, vol 909, (pp. 410-423). Cham: Springer International Publishing. https://doi.org/10.1007/978-3-031-53549-9_39

[21] Mou, C., Liang, A., Hu, C., Meng, F., Han, B., & Xu, F. (2023). Monitoring endangered and rare wildlife in the field: A foundation deep learning model integrating human knowledge for incremental recognition with few data and low cost. *Animals*, *13*(20), 3168. https://doi.org/10.3390/ani13203168

[22] Nathan, R., Monk, C. T., Arlinghaus, R., Adam, T., Alós, J., Assaf, M., ... & Jarić, I. (2022). Big-data approaches lead to an increased understanding of the ecology of animal movement. *Science*, *375*(6582), eabg1780.

[23] Nazir, S., & Kaleem, M. (2021). Advances in image acquisition and processing technologies transforming animal ecological studies. *Ecological Informatics*, *61*, 101212. https://doi.org/10.1016/j.ecoinf.2021.101212

[24] Rafiq, K., Pitcher, B. J., Cornelsen, K., Hansen, K. W., King, A. J., Appleby, R. G., ... & Jordan, N. R. (2021). Animal-borne technologies in wildlife research and conservation. *Conservation technology*, *105*.

[25] Ronoh, E. (2023). *Development of early warning system for human wildlife conflict using deep learning, IoT and SMS* (Doctoral dissertation, NM-AIST).

[26] Roy, R. R., Raman, R., Amanullah, M., Pandey, V. K., & Ganesh, E. N. (2023, November). IoT Applications in Wildlife Conservation: Tracking and Protecting Endangered Species. In *2023 7th International Conference on Electronics, Communication and Aerospace Technology (ICECA)* (pp. 1542-1547). IEEE. https://doi.org/10.1109/ICECA58529.2023.10395145.

[27] Salman, R., & Banu, A. A. (2023). DeepQ residue analysis of computer vision dataset using support vector machine. *Journal of Internet Services and Information Security*, *13*(1), 78-84. https://doi.org/10.58346/JISIS.2023.I1.008

[28] Satapathy, S. N., Sunil Kumar, M., Srivastava, M. P., Sharma, S., Mounika, N., Daivagna, U., & Inbathamizh, L. (2025). The effect of agricultural runoff on freshwater biodiversity and ecosystem functioning. *International Journal of Aquatic Research and Environmental Studies*, *5*(1), 440–449. https://doi.org/10.70102/IJARES/V5I1/5-1-40

[29] Srinivas, K., Shashikanth, B., Raghuram, M., & Venumadhav, K. (2023). Animal Wearables and the Transformation of Movement Ecology Through IoT. *Journal of Advanced Zoology*, *44*.

[30] Wang, R., Noguchi, W., Osada, K., & Yamamoto, M. (2023). Deep-learning-based Multi-behavior Classification of Animals for Efficient Health and Welfare Monitoring. *Sensors & Materials*, *35*.

[31] Wu, Z., Zhang, C., Gu, X., Duporge, I., Hughey, L. F., Stabach, J. A., ... & Wang, T. (2023). Deep learning enables satellite-based monitoring of large populations of terrestrial mammals across heterogeneous landscape. *Nature communications*, *14*(1), 3072. https://doi.org/10.1038/s41467-023-38901-y

Authors Biography

Dr.N. Chitra Kiran is a Professor in the Department of Electronics and Communication Engineering at Alliance University, India. Her research interests include communication systems, signal processing, and embedded technologies. She has published extensively in international journals and conferences and is actively involved in guiding research projects and mentoring students in advanced electronics and communication technologies.

Vinay Kumar Sadolalu Boregowda is an Assistant Professor in the Department of Electronics and Communication Engineering at JAIN (Deemed-to-be University), Bangalore. His academic focus includes wireless communication, VLSI design, and digital signal processing. He has published research in reputed journals and is involved in mentoring students and guiding projects in advanced electronics and communication systems.

Jayvadan Vaishnav is an Assistant Professor in the Department of Life Sciences at PIAS, Parul University, Gujarat. His research interests include microbiology, biotechnology, and environmental biology. He has authored several publications and is actively engaged in mentoring students and conducting research aimed at advancing life sciences and sustainable biological applicatons.

Swati Singh is an Assistant Professor at the Maharishi School of Engineering & Technology, Maharishi University of Information Technology, Uttar Pradesh. Her areas of interest include computer science, machine learning, and data analytics. She is involved in teaching, research guidance, and curriculum development, focusing on emerging technologies and their applications in engineering education.

Manpreet Singh is affiliated with the Centre of Research Impact and Outcome at Chitkara University, Punjab. His professional focus includes research evaluation, impact assessment, and academic performance analysis. He contributes to projects enhancing institutional research quality, fostering innovation, and developing strategies for interdisciplinary collaboration in higher education.

Kanika Seth is associated with the Chitkara Centre for Research and Development, Chitkara University, Himachal Pradesh. Her research interests include institutional research strategy, academic analytics, and outcome-based project management. She is involved in supporting interdisciplinary research, improving academic performance, and promoting innovation-driven initiatives within the university.