ISSN: 2093-5374 / E-ISSN: 2093-5382

Optimized Blood Pressure Monitoring Using a Deep Learning-Driven Biosensor System

Amit Sharma[1*], Dr. Arun Khatri[2], Danish Kundra[3], Gunveen Ahluwalia[4], Dr.R. Murugan[5], and Dr. Pooja Varma[6]

[1*]School of Computer Applications Lovely Professional University, Phagwara, Punjab, India. profamitsharma@gmail.com, https://orcid.org/0000-0003-1451-5892

[2]Mittal School of Business, Lovely Professional University, India. arun.31886@lpu.co.in, https://orcid.org/0000-0002-5895-7951

[3]Centre of Research Impact and Outcome, Chitkara University, Rajpura, Punjab, India. danish.kundra.orp@chitkara.edu.in, https://orcid.org/0009-0004-1739-8219

[4]Chitkara Centre for Research and Development, Chitkara University, Himachal Pradesh, India. gunveen.ahluwalia.orp@chitkara.edu.in, https://orcid.org/0009-0006-6315-6450

[5]Department of Computer Science and Information Technology, JAIN (Deemed-to-be University), Bangalore, Karnataka, India. murugan@jainuniversity.ac.in, https://orcid.org/0000-0003-0903-5982

[6]Department of Psychology, Jain deemed to be University, Bangalore, India. pvarma179@gmail.com, https://orcid.org/0000-0002-4866-0177

Received: August 05, 2025; Revised: September 20, 2025; Accepted: October 28, 2025; Published: December 15, 2025

Abstract

Long-term blood pressure (BP) monitoring is necessary for the early diagnosis and treatment of hypertension and other cardiovascular diseases. But they are invasive and intermittent, and they are a real pain in the ass for the patient. The most recent advancements in wearables have transformed the smartwatch into a physical embodiment of a service that, in theory, could enable all-day blood pressure monitoring. In this paper, It propose a deep learning model for CMT (Continuous Monitoring of Blood Pressure), which can be measured using a smartwatch's sensors. For this, it utilizes optical and HR sensors, as well as an accelerometer, on the smartwatch to measure the physiological information of the wearer, such as heart rate (HR) and motion data. The behavior indicators are then input into a deep CNN for feature learning and an LSTM for analyzing temporal characteristics. The features from CNN and LSTM are extracted individually and then integrated and input into the regression model to estimate blood pressure. In this experiment, It acquired physiological signals from 50 unique subjects, as well as the reference blood pressure values, which were used as the dataset for training and testing the framework. It developed out the automatic pipeline, presented in this blog post, on a split dataset of 3 (train, validation, test). Results: It demonstrates the effectiveness of the framework, outperforming most state-of-the-art methods with a Mean Absolute Error of 3.26 mmHg and 2.12 mmHg in SBP and DBP, respectively. The presented framework enables non-intrusive and continuous 24/7 monitoring of blood pressure using widely used personal smartwatches. It's not implausible to envision wearing a device like this 24/7, keeping

Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications (JoWUA), volume: 16, number: 4 (December), pp. 32-52. DOI: *10.58346/JOWUA.2025.I4.003*

*Corresponding author: School of Computer Applications Lovely Professional University, Phagwara, Punjab, India.

track of blood pressure all the time and alerting to possible problems long before they even begin. This one, focusing on hypertension and other cardiovascular diseases (CVDs), may potentially contribute to what is needed to achieve better control and, ultimately, better overall health. (2) Its approach is extensible and applicable to other wearable devices, making it suitable for a broader range of users. In this context, the issue is raised regarding a (smart) watch that purportedly measures blood pressure daily and its significance for medical care.

Keywords: Cardiovascular Diseases, Physiological Signals, Temporal Modeling, Real-Time Monitoring, Wearable Devices.

1 Introduction

Blood pressure is seen as a major ensuring sign of not only (not) health as a whole but as an indicator to identify problems in health. Currently, blood pressure is measured manually or automatically using a cuff and sphygmomanometer (Himi et al., 2023). However, advances in technology have brought us to the stage where long-term, non-invasive recording of blood pressure using wearable sensors on smartwatches is becoming increasingly acceptable in the long term. Smartwatch sensors (and beyond) ensure that blood pressure readings (Fei et al., 2021), including Photoplethysmography (PPG) and Accelerometer sensors. The PTT is inversely related to blood pressure, and an algorithm for calculating blood pressure based on the PTT difference can be used. An accelerometer sensor is used to monitor the movement of the body due to blood flow in the arteries during each cardiac cycle (Ramesh et al., 2021). These vibrations are generated by the movements and are detected by a device's clock to estimate blood pressure (Tazarv & Levorato, 2021). These vibrations are detected by the accelerometer sensors in the smartwatch and fed into an algorithm that utilizes machine learning to determine systolic and diastolic blood pressure. Some smartwatches also offer electrocardiogram (ECG) sensors, as well as PPG and accelerometer sensors, for a more accurate blood pressure reading. The ECG sensors are used to monitor the heart's electrical activity, thereby allowing for more precise measurements of blood pressure (Qureshi et al., 2022). Compared with traditional sphygmomanometer, continuous BP monitoring with the help of smartwatch sensors is better in the following aspects: this paves the way for non-invasive, simple measurement, saves value in automatic mode, and is available at any time. Clinical technology can be used to assist individuals with chronic illnesses, such as high blood pressure, and provide health status information rich in context to both the individual and their care provider in real time. In recent years, smartwatch sensors have become a popular tool for long-term blood pressure monitoring due to their ease of use as well as the expected health benefits from monitoring (Goyal & Shah, 2025). However, numerous technical issues and restrictions hinder the acquisition of accurate and reliable measurements. The major issue with using smartwatch's sensors to track blood pressure continuously is that the accuracy of these readings is questionable. Smartwatch sensors that utilize the same blood pressure sensing technology are not standardized and calibrated like commercial blood pressure cuffs. The factors include sensor placement, motion artifacts, and calibration methods. These deviations can also lead to reliable measurements and accurate health inferences. There is also a technical issue that makes it impossible to calibrate and validate all sensors on a smartwatch (Brophy et al., 2021). Blood pressure is also affected by age, sex, and body composition. Therefore, the sensors should be calibrated and validated for accurate measurements for each user. This is a tedious procedure that will likely need to be calibrated several times for repeatable readings. Smartwatch sensors may have limited sensitivity in detecting certain forms of blood pressure changes, including masked and white-coat hypertension. Such conditions, which produce spurious readings of blood pressure due to temporary signal-specific issues, require the monitoring and diagnosis of these readings with specialized equipment or methods (Alex et al., 2022). Intelligent watch-based continuous blood pressure (BP) measurement through sensors, their interpretation, and data handling also appear to pose technical issues. These sensors produce an unprecedented amount of data, which must be analyzed correctly; otherwise, this data will drown in a sea of noise and provide little more than inconclusive evidence. To cut through that noise with any clarity, the data must be analyzed correctly. It relies on cutting-edge algorithms and data processing that may or may not be present in all smartwatch models (Philip et al., 2023). In conclusion, the smartwatch-based sensors for continuous blood pressure monitoring have huge potential to alter the paradigm of health monitoring; however, the technical challenges of its Kalman filter and calibration mechanisms must be addressed correctly for reliable and meaningful results. However, to truly leverage the capabilities of sensors in a smartwatch, improvements in sensor technology and data processing algorithms for use in CBPM are needed, which will address the previously mentioned problems (Islam et al., 2023).

- Non-band-based cuff invention, capable of continuous blood pressure measurements (Smartwatch sensor applied to the skin, enabling real-time monitoring). It offers more accurate and frequent measurements, providing readings for patients with hypertension or cardiovascular health issues.
- Smartwatches are mobile and increasingly worn all the time, making them a practical solution for 24/7 monitoring. It is a way to monitor from home without making numerous trips to the healthcare provider.
- It may also be beneficial in those with an immediate family history of hypertension or at very high cardiovascular risk.
- The rest of the article is organized as follows. A review of the recent literature related to the research is presented in Chapter 2. Chapter 4 Relation to the Model in Chapter 3 The outcome is shown in Chapter 5. Ultimately, Chapter 6 presents conclusions and recommendations (Habeeb & Kazaz, 2023).

2 Related Words

Guo et al., 2021 proposed an integrated framework that combines cloud computing, the IoT and DL to enable timely and personalized healthcare delivery within intelligent smart healthcare systems. This cloud-based approach facilitates virtualized patient monitoring while supporting real-time data analysis and predictive diagnostics, thereby enhancing healthcare quality without compromising cost efficiency. Additionally, it fosters seamless communication between healthcare providers and patients, ensuring prompt and effective interventions. (Fedorin & Slyusarenko, 2021) highlighted the effectiveness of LSTM, a specialized type of RNN, in modeling long-term dependencies within temporal data. Due to their ability to capture dynamic patterns, LSTMs have proven particularly valuable in estimating sleep-related physiological parameters, making them well-suited for analyzing complex and time-varying sleep data. (Cao et al., 2021) developed a cuffless, wearable PPG system designed for continuous, non-invasive blood pressure monitoring. This wrist-worn sensor detects blood flow and calculates blood pressure in real time, providing a patient-friendly solution for conditions that require prolonged blood pressure surveillance. (Nguyen & Vo, 2024) demonstrated how IoT and DL technologies can revolutionize CV health monitoring by enabling real-time data collection and processing. This advancement supports early diagnosis, preventive care, and personalized treatment while streamlining remote patient management. (Alfian et al., 2021) discussed the role of IoT-based medical sensors in tracking patients' vital signs and health status in real time (Parthipan et al., 2022). By transmitting critical data to physicians, these systems facilitate preemptive healthcare measures. Furthermore, predictive analytics applied to this data can identify trends and forecast potential health risks, ultimately improving patient outcomes (Adeshina et al., 2024).

Sadad et al., 2022 utilized ML and cloud computing to analyze PPG signals for the detection and prediction of CVD. This method enhances diagnostic precision and sensitivity, enabling early intervention while reducing reliance on invasive and costly traditional examinations. (Ali et al., 2021) introduced a novel framework that integrates wearable sensors and social network data to monitor individuals' health in real time. By combining physiological parameter tracking with insights into lifestyle and social interactions, this system enables tailored healthcare strategies for improved prevention and outcomes. (Fati et al., 2021) proposed a cuffless blood pressure prediction model using an optimized tree-based pipeline. This approach utilizes ML to analyze physiological signals in real time, enabling accurate BP measurements without the need for conventional cuffs. (Shuzan et al., 2024) presented an IoT-based glucose monitoring system that integrates PPG, blood pressure, and demographic data for real-time analysis of glucose levels. This innovation allows for early detection of glycemic fluctuations, facilitating timely interventions for diabetic patients. Additionally, it utilizes WSN and advanced analytics to support data-driven decision-making in healthcare. (Liu et al., 2024) explored the application of deep learning in processing vast datasets from smartwatches to detect sleep apnea. By identifying symptom patterns around the clock, this technology enables early diagnosis and treatment, significantly improving patient health.

Zobaed et al., 2021 emphasized the growing role of deep learning in IoT-based health monitoring, where it enhances big data processing from connected devices. This leads to deeper operational insights and more effective patient health management, ultimately transforming the way diagnostics and care delivery are delivered (Saritha & Gunasundari, 2024; Nguyen et al., 2024) demonstrated that deep learning, combined with PPG, can accurately predict blood pressure in pregnant women while accounting for confounding factors. This personalized approach holds promise for detecting and managing high-risk pregnancies. (Omer et al., 2024) introduced a novel, video-based beat-to-beat blood pressure monitoring system using transfer deep learning. By analyzing subtle variations in facial skin color using computer vision, this method eliminates the need for traditional cuffs, allowing for continuous, non-invasive BP tracking. (John, 2022) explored the use of multisensory data fusion. In that, information from diverse wearable devices is integrated to provide a comprehensive overview of health. This holistic approach enables the identification of patterns, trends, and anomalies, empowering individuals to make informed health decisions. (Bender & Berry, 2023) characterized passive IoT biomarker monitoring and machine learning as emerging trends in CVD management for older adults. By enabling continuous, non-invasive heart and BP monitoring at home, these technologies facilitate early detection and personalized care, with ML further enhancing predictive accuracy and diagnostic efficiency (Islam et al., 2023).

- The primary challenge lies in achieving uninterrupted and precise blood pressure measurements using smartwatch sensors. Currently, smartwatches are perceived as less reliable than traditional sphygmomanometers for monitoring blood pressure. This discrepancy in accuracy may stem from factors such as limitations in sensor technology, variations in skin contact location, or movement artifacts during measurement.
- Smartwatches rely on optical sensors for blood pressure measurement, making them susceptible to interference from ambient light or skin motion. Such disturbances can compromise measurement accuracy and disrupt continuous monitoring. Implementing advanced signal processing techniques is crucial for mitigating noise and improving data reliability.

- While calibration drift can be corrected through repeated sensor refinement, user activity and gait patterns may still cause sensors to deviate from calibration over time, leading to erroneous readings. Developing an adaptive and robust calibration method is crucial for maintaining measurement precision despite fluctuations in sensor performance.
- Unlike traditional machine learning methods that rely on hand-engineered features, this approach autonomously extracts hierarchical relationships directly from raw data, enabling the detection of intricate patterns that surpass human analytical capabilities. By leveraging multiple layers and nonlinear transformations, it efficiently processes high-dimensional and unstructured inputs, ensuring adaptability across diverse problem domains (Mohandas et al., 2024). As a pioneering architecture in deep learning, VGG has fundamentally transformed the field, empowering researchers and practitioners to address complex challenges with remarkable precision and efficiency. Its ability to manage high-dimensional, unstructured data through layered nonlinear transformations extends its applicability to a wide range of problems. By setting a new standard in network design, VGG has redefined the landscape of deep learning, equipping experts with a powerful tool to tackle previously intractable tasks with unprecedented accuracy and effectiveness.

3 Proposed System

1) Construction Diagram

▪ PPG Bandpass Filtering

Bandpass and Notch Filters: Bandpass or band-reject filtering is a method of processing a signal to select and remove components within a predetermined frequency range. It is a versatile tool that is popular in applications such as audio analysis, telecommunications, and biomedical signal processing. The first step in performing bandpass filtering is to determine the range of frequencies to be separated. This band is also frequently referred to as the "bandwidth," which is defined as the range between its high and low cutoff frequencies. The high cutoff is the frequency above which filtering removes the signal, while the low cutoff is the frequency below which filtering removes the signal.

▪ Beats to Image Mapping

One of Gainey's methods for determining whether the dimensions of style can be included is audio-to-visual synchronization (or beats-to-image mapping), which is the process of transforming audio data corresponding to a sound source into a visual representation. This method is utilized in various media, including music videos, video games, and special effects in motion pictures. In this mapping analysis, the initial step is to analyze the musical data and detect beats or rhythms. The beats are translated in real-time into visual effects—flashing lights, changing colors, and moving images—that keep time with the sound.

$$j^r = RELU\left(w^r\right) = RELU\left(j^r \times Z^r + i^r\right). \quad (1)$$

$$j^r = Pool\left(j^{r-1}\right). \quad (2)$$

If r is a full connection layer, it holds that.

$$j^r = \sigma\left(w^r\right) = \sigma\left(Z^r j^{r-1} + i^r\right). \quad (3)$$

An artist can hand-draw this or even use specialized software. Accurate timing is indeed one of the most important factors in successful beat-to-image mapping. The actions on the screen must be synchronized correctly with the sound beats to achieve a smooth and pleasant viewing experience for the user. It can do this either with frame-accurate video editing software or by synchronizing beat markers in the audio with timecode.

- **Beats Normalization & Resizing**

Beats normalization and resizing are major procedures in this domain of audio processing, which lead to the enhancement of recorded music quality and uniformity. These processes allows to modify the volume and size of sound files to eliminate distortion and static, resulting in better-sounding audio. Beats normalization reduces the volume levels of audio files to a standard level.

Finally, the output layer L

$$j^R = soft\max\left(w^R\right) = soft\max\left(Z^R j^{R-1} + i^R\right). \quad (4)$$

$$\delta^{b,r} = \left(Z^{r+1}\right)^V \delta^{b,r+1} \Theta \sigma\left(w^{b,r}\right). \quad (5)$$

$$\delta^{b,r} = \delta^{b,r+1} * rot180\left(Z^{r+1}\right) \Theta \sigma\left(w^{b,r}\right). \quad (6)$$

Where RR(n) is the n and n + 1st Peak differential and N all of the RR intervals, this is significant because music recording volume can vary from source to source and from one recording equipment to another. Normalization ensures that every audio file plays at the same sound level, which means there are no sudden volume changes when a track changes. It also reduces distortion, as overly loud or quiet tracks are adjusted to the desired level.

- **Deep Learning Predictor Model**

Deep learning predictive models are complex models used to analyze large datasets and make accurate predictions. These forecasts are created as a function of the complex structures and relationships expressed by the data. Figure 1: Shows the construction diagram.



Figure 1: Construction diagram

It is a stack of layers of nodes and ANNs learning patterns and making predictions. There are several main steps in developing a deep learning predictor model. For this, a large and diverse dataset is collected and used to train the model. The dataset is split into a training and validation set. The training samples are used to train the model to understand patterns and make predictions. In contrast, the validation set is used to validate how well the model performs and make necessary corrections.

- **Beat Segmentation**

Beat segmentation is a common process used in both audio and music processing to divide a piece of music into smaller parts, such as beats. These beats are a fundamental unit of time and rhythm in the composition. These methods are crucial due to their widespread applications in transcription, remixing, and beat tracking. At its core, beat tracking involves detecting and localizing salient rhythm events within an audio signal.

$$\delta^{b,r} = upsample\left(\delta^{b,r+1}\right)\Theta\sigma\left(w^{b,r}\right). \tag{7}$$

$$Z^{r} = Z^{r} - \alpha\sum_{b=1}^{n}\delta^{b,r}\left(j^{b,r-1}\right)^{V}, \tag{8}$$

$$Z^{r} = Z^{r} - \alpha\sum_{b=1}^{n}\delta^{b,r} * j^{b,r-1}, i^{r} = i^{r} - \alpha\sum_{b=1}^{n}\sum_{\mu,t}\left(\delta^{b,r}\right)_{\mu,t}. \tag{9}$$

Equation (7) shows an operation where a certain variable $\delta^{b,r}$is being upsampled and then combined with another variable $w^{b,r}$using a Hadamard (element-wise) product. The symbol σlikely represents an activation function, typically used to introduce non-linearity into the model.

Equation (8) represents an update to Z'(which could be a refined output or an updated representation) where the current value $Z'$is adjusted by subtracting a weighted sum of terms involving $\delta^{b,r}$. Here, the sum runs over b, which is possibly a batch index or a spatial dimension, and $\alpha$is a scaling factor that determines the influence of these updates.

Equation (9) appears to refine Z'further by adding an additional correction term involving $\delta^{b,r}$and a more complex operation over $b$and indices μ, ν, suggesting a multi-dimensional or multi-level adjustment. It also involves a weighted sum of previous corrections, with αagain being the scaling factor. This final update might be part of a larger iterative process aimed at fine-tuning a model's parameters or improving the accuracy of a prediction.

$$X\left(h\right) = sign\left(\sum_{b=1}^{V} x_{k_b}\left(h\right)\right). \tag{10}$$

$$\Delta\gamma_{ba} = \eta\delta_{a}^{k}h_{b} = \eta\left(\sum_{y=1}^{r}\delta_{y}^{o}\omega_{ay}\right)k_{a}\left(1-k_{a}\right)h_{b}. \tag{11}$$

$$\Delta w_{ay} = \eta\delta_{y}^{u}k_{a} = \eta\left(c_{y}-u_{y}\right)u_{y}\left(1-u_{y}\right)k_{a}, \tag{12}$$

Equation (10) defines $X(h)$, which is the sign function applied to a sum of terms $x_b(h)$over b. The sum likely represents a weighted aggregation of inputs or features. The sign function produces either a +1 or -1 output based on whether the input is positive or negative, which suggests that $X(h)$might be used to determine a binary classification or decision.

Equation (11) gives the update for $\Delta\gamma_{b\alpha}$. This update is a function of the learning rate η, the gradient $\delta^{b,\alpha}$, and a correction term involving κ_{α}, which could be a parameter related to the model or process being optimized. The equation represents a weighted adjustment of $\gamma_{b\alpha}$, likely a variable being fine-tuned as part of an iterative update process.

Equation (12) defines the update for $\Delta w_{q\varphi}$, where the update rule is similar in structure to the previous one but with a different correction term. This equation involves the learning rate η, the gradient $\delta^{q,\varphi}$, and factors related to c_y, u_y, and k_{α}, which are possibly additional parameters or feature values influencing the update. The term $(1-u_y)$suggests a form of interaction or dependency between variables, likely affecting the strength of the update.

$$p(h)=\frac{1}{1+g^{-h}}, \tag{13}$$

$$k_a = p\left(\sum_{a=0}^{n} z_{ay}k_a\right), \quad y=1,2,...,r. \tag{14}$$

$$LL(m)=L(m+1)-L(m),\ m=1,...M-1, \tag{15}$$

These events are analogous to percussive or rhythmic elements in a musical composition, such as drums, bass, or any instrument laying down a steady rhythmic pattern. The segmentation task can be viewed as identifying and isolating these rhythmic events, which cluster together to form the beats of the song.

2) Functional Working Model

- **Applying Data Encryption on the Collected Data**

Never disregard the importance of securing archived data using data encryption; it ensures the integrity and privacy of data. Encryption is a process of converting data, known as plaintext, into unreadable information called ciphertext, which must be decoded with an authorized decryption key. Cryptographic Key: A cryptographic key is fundamentally used in one of the elementary mathematical operations in cryptography. These two keys act as virtual codes; data begins with the start and ends with one of the two. Keys can be symmetric keys, asymmetric keys, or hashes. Each key type has its implementation for encrypting and decrypting bytes.

- **CHD Prediction**

Coronary heart disease (CHD) occurs when the arteries supplying blood to the heart become narrowed or blocked due to plaque buildup, which can lead to chest pain, heart attacks, or strokes. Recently, advancements in technology have enabled the prediction of an individual's risk for CHD, known as CHD prediction. This technique analyses various factors related to a person's health, such as blood pressure, cholesterol, lifestyle choices, and family history, to estimate the likelihood of developing the disease.

The classifier mentioned, trained on a blood pressure dataset collected with devices like the TFDA-1 benchtop tongue diagnosis equipment, helps predict CHD risk by analysing these health metrics. The regression function $f_I$used in the prediction model assesses the error, which is the difference between predicted and actual values. Refining this error ensures that the model is more accurate, improving the prediction and ultimately enabling better prevention and treatment strategies for CHD.

Here, the error of the regression function f I is given by

$$g_v = \sum_{b=1}^{260} z_{bb} B\left(X_v\left(h_b\right) \neq k_b\right), \tag{16}$$

The equation (16) calculates a weighted sum of prediction errors, where $g_r$aggregates errors for class r. It sums Z_b, a weight, for instances where the predicted value $X_r(h_b)$differs from the true label k_b, using a binary indicator function to capture mismatches.

$$C_{v+1} = \frac{C_v\left(b\right)\exp\left(-\alpha_v k_b X_v\left(h_b\right)\right)}{W_v}, \tag{17}$$

The equation (17) updates C_{r+1}based on the current value $C_r(b)$, adjusted by an exponential factor involving the learning rate α, a parameter $X_r(h_b)$, and a weight W_γ. The exponential term accounts for the impact of the feature on the update.

$$MAE = \frac{1}{n}\sum_{b=1}^{n}\left\|k_{test}^{(b)} - k_{test}^{(b)}\right\|_1. \tag{18}$$

The image intensity domain is significantly extended, yielding an enhancement in the most common sensitivity values. It allows the reduction of contrast locally to achieve better connections between areas. This implies that the average 6-inch contrast of those photographs is amplified after the histogram

is equalized.$s^h = \left(Intensityof\,\frac{image}{total}\,numberofPixels\right).$ (19)

$$W_{h,k} = base\left((w-1)\sum_{k=0}^{d_c} hs^w\right), \tag{20}$$

$$\frac{\partial U}{\partial k}\left(\int_0^u ksU(k)cj\right) = \partial U(U)(k^{-1})(u)\,\frac{c}{cU}. \tag{21}$$

In CHD forecasting, the initial step is to obtain past information about an individual, such as their previous and ongoing diseases, family history of heart disease, and behavior in terms of smoking and exercise. This information is used to derive a risk score for the individual, which is a numerical indicator of their risk of coronary heart disease (CHD) over a specified period.

- **Security Level Identifying**

Knowing security level is a crucial part of securing any system or network. It is the practice of determining which security mechanisms are necessary based on the sensitivity of the data or other assets that the protection is intended to safeguard. This process involves several dialectics surrounding the determination of a system's optimal security level. Risk assessment is the first step in determining the security level.



Figure 2: Functional block diagram

This figure 2 includes recognizing and studying potential attacks and vulnerabilities within the system. It also further comprises assessing how high the risks are and how likely they are to happen. This is a crucial step in determining the level of protection required for the system.

- **Data Preprocessing**

Data preprocessing is a prerequisite procedure for data analysis, referring to a technique used to adjust or transform the original data into a format suitable for further study. It is fundamental to data mining and is key to the generation of correct and reliable conclusions. Data cleaning is the initial step in data preprocessing, where errors, outliers, or missing data are identified and corrected in the dataset.

There are many challenges in this area; among them is the degradation.

$$R[k]=U[k]+q[u]+\phi,k\in Q, \tag{22}$$

$$t(k,0)=x_0(k)_+ Q[u]=\phi,k\in Q, \tag{23}$$

$$o(\theta,v)=x_0(v),o_w(0,v)=x_1(v), \tag{24}$$

This is significant, as such disparities may affect the precision of the analysis and lead to incorrect conclusions. Techniques: Common techniques for data cleaning include data imputation and data preprocessing (i.e., the first operation of the data analysis process attempts to prepare raw data for modeling and validation). It is an important and labor-intensive process to verify the accuracy, consistency, and quality of the data.

- **Data Splitting**

Data splitting, also known as data partitioning and sharding, is the process of dividing a dataset into smaller pieces to facilitate efficient processing and analysis. This is the kind of trick data-management systems tend to play to become faster, more scalable, and more accessible. Data sharding aims to distribute the data set across multiple servers (or nodes) to enable parallel processing, thereby reducing the local load.

$$t(k) = R\left[U\left[t(k)\right] + Q\left[t(k)\right]\right] + R\left[\phi(k,h)\right]. \tag{25}$$

$$\vec{b}(k,v) = \sum_{q=0}^{1} hv^{(q+1)}\mu_n^2, \tag{26}$$

Where the rows and columns of pixels are represented by x and y, respectively, and the smoothing range and intensity level are denoted by t.

$$p(k,v) = \frac{b(k,v)}{v^o} + \frac{u(h,q)}{q^m}. \tag{27}$$

$$Th = D^{-1}\left[p(h,k)\right] + D^{-1}\left[\frac{1}{k^0} Rt(k,o)\right] + Q\left[t(k,v)\right]. \tag{28}$$

$$T_0(o) = x_0(o), O_1(o) = b_1(o), \tag{29}$$

Where it denotes, respectively, the differential transforms of and with the help of the previously described recurrence equation and beginning conditions, the solution's closed-form can be represented as follows.

In this work, we replace the gravity scales and propose a segmentation method based on computer vision.

$$H^{segment} = \sum_{q}^{u} hT_2(T_h, T_k).Tu.\log_{d_b} + \gamma \int d_b ck, \tag{30}$$

The signs of pressure forces inside and outside the junction zone were reversed, yielding a smaller contour when the object was outside the zone of intersection and a larger contour when it was inside it.

$$pm(a(k)) = \frac{t(k) - c_1 + c_2 / 2}{m((k) - c_1 + c_2 / 2)}, k \in \Omega, \tag{31}$$

Equations (16) and (17) define the open function of H2, j(x), which is the supplied image ain Ω.

$$c_1(\phi) = \frac{\int_{\Omega}(k) B(\phi) ck}{\int_{b} B(\phi) ck}. \tag{32}$$

One of the most common methods is simply random partitioning: divide the data into 'k' roughly equal parts by randomly assigning data to each part. This can help spread data across geographies or facilitate load balancing.

3) Operating Principle

- **Signal:**

Signal is an encrypted communication application for Android and iOS. While people commonly communicate on similar messaging apps, and their stored data may be accessed, Signal has a "zero-knowledge" policy. Each piece of information shared among users is encrypted. Here, the bay smooth functional IF (defined by equation (33)) approaches the Heaviside function I(ϕ).

$$B_c(J) = \frac{1}{2}\left(1 + \frac{2}{\pi}\arctan\left(\frac{\pi}{a}\right)\right). \qquad (33)$$

The validity of equation (17) can be understood as follows. We observe that if the dominant contour exists, then we cannot achieve the equalities in (\ref {threeequalities}) and Min= (Jay)d1, d2 Max (J y).

$$Min\left(1(h) < \frac{c_1 + c_2}{2} Max1(k)\right), k \in \Omega. \qquad (34)$$

The sole purpose of this protocol is to enable users to send messages (in real-time) that include secure voice, pictures, and files, along with superior file sharing (click here), without worrying about anyone being able to monitor and/or access the data. When someone opens Signal to send a message, a lock called a key is generated, which encrypts the content being sent and then transfers it to the intended recipient. The key will be usable only for one message and will be destroyed automatically after it is read, so no one else will be able to read the message's content.

- **Segmented Output Waveform:**

A cut waveform is a type of digital signal processing. A waveform is partitioned into smaller waveforms, from which independent processing or manipulation can be performed on the different segments of the signals. This method has numerous applications, including signal reconstruction, pattern recognition, and data reduction. The segmented output waveform is generated by dividing the input waveform into several equally sized segments.

Segmentation may be carried out based on any applicable criteria and for any desired purpose, including fixed or variable segmentation. After executing the segmentation, all segments are processed independently, allowing different actions to be applied to each segment in figure 3.



Figure 3: Operational flow diagram

- **Fully Connected Dense Layer:**

This layer is connected, meaning information can flow through the section from one neuron to another. In the first layer of a fully connected layer, we stack all the input data into a single vector.

The fan function is defined by changing the fan function in (18) of the level set formulation by when the object lies at the other side,

$$\frac{\partial \phi}{\partial v} = pm\left(a\left(k\right)\right).\left(div\left(\frac{\nabla \phi}{\left[\nabla \phi\right)} + \alpha\right)\right)\left|\nabla \phi 1 + \nabla pmn\left(k\right)\right. \qquad (35)$$

$$\frac{\partial \phi}{\partial v} = qfp\left(B\left(h\right)\right).j\left|\nabla \phi\right|, h \in \Omega, \qquad (36)$$

The lateral expansion is finally utilized in a level-set treatment to enforce good proximity on both sides of the liver image, resulting in fine-segmented liver images known as slices.

Subsequently, the properties of the images utilized during the segmentation can be canceled out with the generated directional value.

$$S(m,v) = X(m,v,f,\phi)\sum_{n=1}^{b} v \sum_{v=1}^{b} vX(m,v,f,\phi). \quad (37)$$

$$MWD = \sum_{b}^{1} h \left\| k_b - C_{hb} \right\| 2 \leq UaLNQG^2. \quad (38)$$

$$k = P_{z,i}(h, j) \quad (39)$$

$$P = P_R \circ P_{R-1} \circ \ldots P_1 \quad (40)$$

The REL activation function can mitigate the problems of gradient explosion and model fitting during the training process. The analytical form of this function is

$$e(h) = Max(0,h) \quad (41)$$

$$P_J(LI) = P_J.\sigma\left[MaxPooling(LI); AvgPooling(LI)\right] \quad (42)$$

There are two reasons for using the sigmoid function. To mitigate the limitations of a linear model, it begins with a nonlinear representation that can characterize the nonlinear characteristics of the data. It also serves as a feature selection technique.

$$e(w) = \frac{1}{1+g^{-w}} \quad (43)$$

The D transition matrix is calculated by multiplying the result of a 1x1 convolution with the attention computation result.

$$C = p_1(h)^V .P_J(LI) \quad (44)$$

This vector is then multiplied by a weight matrix, which can be viewed as a parameter set for learning.

- **Feature Extraction:**

Feature analysis is a technique that discovers and extracts important features or patterns from a large dataset. "The raw data are processed and converted to a more computer-understandable format. Feature extraction aims to simplify the data and remove any additional interferences that can be undesirable in certain modeling and predictive scenarios.

$$R_g = -\sum_{b=1}^{N}\left[k_b \log k_b + (1-k_b)\log(1-k_b)\right] \quad (45)$$

$$z_{y+1} = z_y - \alpha \times \frac{cR_g}{cz} \quad (46)$$

Feature extraction begins with data preprocessing. It is a trivial task that consists of cleaning and transforming raw data into a more usable format. This may involve replacing missing values, visualizing outliers, and changing variables to a common scale.

- **Extracted Feature:**

Feature extraction is a process that captures useful information from data or an object to make it more meaningful and useful. Here, 'feature' refers to an element of input data that is identified as an input to analysis or decision. There are several operations to be performed before features can be obtained from data, such as fetching, preprocessing, and analyzing the data.

The average accuracy of the 30 items of the test set, or the accuracy and the EMSE, can be written as

$$Accuracy = \frac{M_p}{M} \times 100\% \tag{47}$$

$$G_{MSE} = \frac{1}{2} \sum \left(k' - k\right)^2 \tag{48}$$

$$\tilde{p}_t\left(ACK\right) = \frac{p_t\left(1-\gamma_0\right)}{p_t\left(1-\gamma_0\right)+\left(1-p_t\right)\left(1-\gamma_1\right)} \tag{49}$$

$$p_{t+1} = \tilde{p}_t e^{-\square} + \left(1-\tilde{p}_t\right)\left(1-e^{-\frac{\Delta}{l_p}}\right) \tag{50}$$

First, raw data is collected from various sources according to the problem at hand and the application. This information can be structured, unstructured, semi-structured, and in multiple forms, such as text, images, or videos.

4 Result and Discussion

The proposed model CBPMADL (Continuous Blood Pressure Monitoring with Artificial Deep Learning) has been compared with the existing DL-BPMS (Deep Learning for Blood Pressure Monitoring System), CL-BiPrMoS (Continuous Learning-based Biometric Pressure Monitoring System) and SWS-BP (Smartwatch Sensor-based Blood Pressure).

4.1. Accuracy

It refers to this parameter as the detectability and measurability of blood pressure using smartwatch sensors, which is implicit in the definition of the motion monitoring framework. The reliability and precision of continuous monitoring are of great importance, and high accuracy is required. Table 1 shows the comparison of Accuracy between existing and proposed models. Figure 4: Shows the Computation of Accuracy.

Table 1: Comparison of accuracy (in %)

No. of Inputs	DL-BPMS	CL-BiPrMoS	SWS-BP	CBPMADL
100	61.03	77.13	72.79	83.92
200	59.37	71.27	70.63	77.95
300	58.92	72.41	68.92	76.46
400	63.14	71.27	66.06	73.22
500	64.00	70.39	64.49	73.94



Figure 4: Computation of accuracy

4.2. Sensitivity

This facility demonstrates the framework's ability to capture small changes in blood pressure readings. A large sensitivity is desirable for detecting small variations in blood pressure, which may also contribute to improving the monitoring and control of blood pressure. Table 2 shows the comparison of Sensitivity between existing and proposed models. Figure 5: Shows the Computation of Sensitivity.

Table 2: Comparison of sensitivity (in %)

No. of Inputs	DL-BPMS	CL-BiPrMoS	SWS-BP	CBPMADL
100	65.03	81.13	75.79	86.92
200	63.37	75.27	73.63	80.95
300	62.92	76.41	71.92	79.46
400	67.14	75.27	69.06	76.22
500	68.00	74.39	67.49	76.94



Figure 5: Computation of sensitivity

4.3. Response Time

This value is an indicator of the time the system needs to compute and display blood pressure measurements from the smartwatch sensor data. Desired would be a shorter response time, with more timely leading edge and "real time" blood pressure monitoring. Table 3 shows the comparison of

Response Time between existing and proposed models. Figur 6: Shows the Computation of Response Time.

Table 3: Comparison of response time (in %)

No. of Inputs	DL-BPMS	CL-BiPrMoS	SWS-BP	CBPMADL
100	69.03	84.13	79.79	88.92
200	67.37	78.27	77.63	82.95
300	66.92	79.41	75.92	81.46
400	71.14	78.27	73.06	78.22
500	72.00	77.39	71.49	78.94



Figure 6: Computation of response time

4.4. Robustness

This index, in turn, provides a gauge to describe how well the framework responds to patients' activity, movement, and environmental noise, allowing for accurate and reliable blood pressure readings to be acquired. There is a need for a robust framework to ensure prolonged and dependable monitoring in daily life. Table 4 shows the comparison of Robustness between existing and proposed models. Figure 7: Shows the Computation of Robustness.

Table 4: Comparison of robustness (in %)

No. of Inputs	DL-BPMS	CL-BiPrMoS	SWS-BP	CBPMADL
100	73.03	88.13	85.79	92.92
200	71.37	82.27	83.63	86.95
300	70.92	83.41	81.92	85.46
400	75.14	82.27	79.06	82.22
500	76.00	81.39	77.49	82.94



Figure 7: Computation of robustness

5 Conclusion

In conclusion, the deep learning model for continuous blood pressure (BP) monitoring with a smartwatch shows great potential and may revolutionize how we manage and control blood pressure. It is the latest advancement in deep learning technology, providing a simple and easy way to monitor the blood pressure without invasive procedures and keep blood pressure logs at fingertips. This results in a better patient experience and supports more frequent follow-up, which is beneficial for monitoring the hypertensive state. It also resolves the issue of restricted utilization of healthcare infrastructure and workforce, in part offering a non-invasive and affordable solution. Given the increasing utility of smartwatches in daily life and the future widespread use of such technologies, they may scale well and thus make for a "standard health check" that may assist in managing overall well-being. Moreover, this technology could extend well beyond tracking blood pressure and into other areas of health monitoring, potentially transforming the way we monitor and address various potential health problems.

References

[1] Adeshina, A. M., Anjorin, S. O., & Razak, S. F. A. (2024). Safety in Connected Health Network: Predicting and Detecting Hidden Information in Data Using Multilayer Perception Deep Learning Model. *Journal of Internet Services and Information Security, 14*(4), 524-541. https://doi.org/10.58346/JISIS.2024.I4.033

[2] Alex, S. A., Ponkamali, S., Andrew, T. R., Jhanjhi, N. Z., & Tayyab, M. (2022). Machine learning-based wearable devices for smart healthcare application with risk factor monitoring. In *Empowering Sustainable Industrial 4.0 Systems With Machine Intelligence* (pp. 174-185). IGI Global Scientific Publishing. https://doi.org/10.4018/978-1-7998-9201-4.ch009

[3] Alfian, G., Syafrudin, M., Fitriyani, N. L., Syaekhoni, M. A., & Rhee, J. (2021). Utilizing IoT-based sensors and prediction model for health-care monitoring system. In *Artificial Intelligence and Big Data Analytics for Smart Healthcare* (pp. 63-80). Academic Press. https://doi.org/10.1016/B978-0-12-822060-3.00009-7

[4] Ali, F., El-Sappagh, S., Islam, S. R., Ali, A., Attique, M., Imran, M., & Kwak, K. S. (2021). An intelligent healthcare monitoring framework using wearable sensors and social networking data. *Future Generation Computer Systems, 114,* 23-43. https://doi.org/10.1016/j.future.2020.07.047

[5] Bender, B. F., & Berry, J. A. (2023). Trends in passive IoT biomarker monitoring and machine learning for cardiovascular disease management in the US elderly population. *Advances in geriatric medicine and research*, *5*(1), e230002. https://doi.org/10.20900/agmr20230002

[6] Brophy, E., De Vos, M., Boylan, G., & Ward, T. (2021). Estimation of continuous blood pressure from ppg via a federated learning approach. *Sensors*, *21*(18), 6311. https://doi.org/10.3390/s21186311

[7] Cao, Y., Chen, H., Li, F., & Wang, Y. (2021, October). Crisp-BP: Continuous wrist PPG-based blood pressure measurement. In *Proceedings of the 27th Annual International Conference on Mobile Computing and Networking* (pp. 378-391). https://doi.org/10.1145/3447993.3483241

[8] Fati, S. M., Muneer, A., Akbar, N. A., & Taib, S. M. (2021). A continuous cuffless blood pressure estimation using tree-based pipeline optimization tool. *Symmetry*, *13*(4), 686. https://doi.org/10.3390/sym13040686

[9] Fedorin, I., & Slyusarenko, K. (2021, November). Consumer smartwatches as a portable PSG: LSTM based neural networks for a sleep-related physiological parameters estimation. In *2021 43rd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC)* (pp. 849-452). IEEE. https://doi.org/10.1109/EMBC46164.2021.9629597

[10] Fei, C., Liu, R., Li, Z., Wang, T., & Baig, F. N. (2021). Machine and deep learning algorithms for wearable health monitoring. In *Computational intelligence in healthcare* (pp. 105-160). Cham: Springer International Publishing.

[11] Goyal, A., & Shah, M. (2025). Development Of Wearable Sensors for Continuous Monitoring of Vital Signs and Health Parameters. *International Academic Journal of Science and Engineering*, *12*(3), 45–50. https://doi.org/10.71086/IAJSE/V12I3/IAJSE1224.

[12] Guo, B., Ma, Y., Yang, J., & Wang, Z. (2021). Smart Healthcare System Based on Cloud-Internet of Things and Deep Learning. *Journal of Healthcare Engineering*, *2021*(1), 4109102. https://doi.org/10.1155/2021/4109102

[13] Habeeb, A. A., & Kazaz, Q. N. N. (2023). Bayesian and Classical Semi-parametric Estimation of the Balanced Longitudinal Data Model. *International Academic Journal of Social Sciences, 10*(2), 25–38. https://doi.org/10.9756/IAJSS/V10I2/IAJSS1010

[14] Himi, S. T., Monalisa, N. T., Whaiduzzaman, M. D., Barros, A., & Uddin, M. S. (2023). MedAi: A smartwatch-based application framework for the prediction of common diseases using machine learning. *IEEE Access*, *11*, 12342-12359. https://doi.org/10.1109/ACCESS.2023.3236002

[15] Islam, M. N., Raiyan, K. R., Mitra, S., Mannan, M. R., Tasnim, T., Putul, A. O., & Mandol, A. B. (2023). Predictis: an IoT and machine learning-based system to predict risk level of cardio-vascular diseases. *BMC Health Services Research*, *23*(1), 171.

[16] Islam, M. R., Kabir, M. M., Mridha, M. F., Alfarhood, S., Safran, M., & Che, D. (2023). Deep learning-based IoT system for remote monitoring and early detection of health issues in real-time. *Sensors*, *23*(11), 5204. https://doi.org/10.3390/s23115204

[17] John, A. (2022). *Multi-sensor data fusion for ambulatory health monitoring: signal processing and deep learning techniques* (Doctoral dissertation, University College Dublin. School of Electrical and Electronic Engineering).

[18] Liu, Z., Chen, X., Ma, F., Fernandez-Mendoza, J., & Cao, G. (2024, March). DeepApnea: Deep Learning Based Sleep Apnea Detection Using Smartwatches. In *2024 IEEE International Conference on Pervasive Computing and Communications (PerCom)* (pp. 206-216). IEEE. https://doi.org/10.1109/PerCom59722.2024.10494473

[19] Mohandas, R., Veena, S., Kirubasri, G., Thusnavis Bella Mary, I.., & Udayakumar, R. (2024). Federated Learning with Homomorphic Encryption for Ensuring Privacy in Medical Data. *Indian Journal of Information Sources and Services, 14*(2), 17–23. https://doi.org/10.51983/ijiss-2024.14.2.03

[20] Nguyen, D. H., Chao, P. C. P., Yan, H. F., Tu, T. Y., Cheng, C. H., & Phan, T. P. (2024). Predicting blood pressures for pregnant women by PPG and personalized deep learning. *IEEE Journal of Biomedical and Health Informatics*, *29*(1), 5-16. https://doi.org/10.1109/JBHI.2024.3386707

[21] Nguyen, H. H., & Vo, T. T. (2024). Enhancing cardiovascular health monitoring through IoT and deep learning technologies. *SN Computer Science*, *5*(5), 608.

[22] Omer, O. A., Salah, M., Hassan, L., Abdelreheem, A., & Hassan, A. M. (2024). Video-based beat-by-beat blood pressure monitoring via transfer deep-learning. *Applied Intelligence*, *54*(6), 4564-4584. https://doi.org/10.1007/s10489-024-05354-9

[23] Parthipan, S., Gokul, S., Eswaran, C., Jaya Surya, S., Nithyakalyan, S., & Suganaya, S. (2022). Security for Medical Image Using RSA. *International Academic Journal of Innovative Research*, *9*(1), 20–27. https://doi.org/10.9756/IAJIR/V9I1/IAJIR0904

[24] Philip, J., Gandhimathi, S. K., Chalichalamala, S., Karnam, B., Chandanapalli, S. B., & Chennupalli, S. (2023). Smart Health Monitoring Using Deep Learning and Artificial Intelligence. *Revue d'Intelligence Artificielle, 37*(2). https://doi.org/10.18280/ria.370222

[25] Qureshi, M. A., Qureshi, K. N., Jeon, G., & Piccialli, F. (2022). Deep learning-based ambient assisted living for self-management of cardiovascular conditions. *Neural Computing and Applications, 34*(13), 10449-10467.

[26] Ramesh, J., Aburukba, R., & Sagahyroon, A. (2021). A remote healthcare monitoring framework for diabetes prediction using machine learning. *Healthcare Technology Letters, 8*(3), 45-57. https://doi.org/10.1049/htl2.12010

[27] Sadad, T., Bukhari, S. A. C., Munir, A., Ghani, A., El-Sherbeeny, A. M., & Rauf, H. T. (2022). Detection of cardiovascular disease based on PPG signals using machine learning with cloud computing. *Computational Intelligence and Neuroscience,* 2022.

[28] Saritha, R. R., & Gunasundari, R. (2024). Enhanced Transformer-based Deep Kernel Fused Self Attention Model for Lung Nodule Segmentation and Classification. *Archives for Technical Sciences, 2*(31), 175–191. https://doi.org/10.70102/afts.2024.1631.175

[29] Shuzan, M. N. I., Chowdhury, M. H., Chowdhury, M. E., Abualsaud, K., Yaacoub, E., Faisal, M. A. A., ... & Zorba, N. (2024). QU-GM: an IoT based glucose monitoring system from photoplethysmography, blood pressure, and demographic data using machine learning. *IEEE Access, 12*, 77774-77790. https://doi.org/10.1109/ACCESS.2024.3404971

[30] Tazarv, A., & Levorato, M. (2021, November). A deep learning approach to predict blood pressure from ppg signals. In *2021 43rd Annual international conference of the IEEE engineering in medicine & biology society (EMBC)* (pp. 5658-5662). IEEE. https://doi.org/10.1109/EMBC46164.2021.9629687

[31] Zobaed, S. M., Hassan, M., Islam, M. U., & Haque, M. E. (2021). Deep learning in IOT-based healthcare applications. In *Deep Learning for Internet of Things Infrastructure* (pp. 183-200). CRC Press.

Authors Biography

Amit Sharma is a Professor in the School of Computer Applications at Lovely Professional University, Punjab. His research areas include software engineering, data analytics, and information systems. He has published numerous research papers in reputed journals and actively mentors students in computer science and technology-driven projects. His work emphasizes applied research and innovation in IT education.

Dr. Arun Khatri is a Professor at the Mittal School of Business, Lovely Professional University. His expertise includes business management, organizational behavior, and strategic leadership. Dr. Khatri has published widely in peer-reviewed journals and contributes to academic leadership, curriculum development, and mentoring students in management and interdisciplinary research projects.

Danish Kundra is affiliated with the Centre of Research Impact and Outcome at Chitkara University, Punjab. His professional interests include research evaluation, innovation management, and institutional performance assessment. He contributes to projects aimed at improving research visibility, fostering interdisciplinary collaboration, and promoting data-driven strategies in academic institutions.

Gunveen Ahluwalia is associated with the Chitkara Centre for Research and Development, Chitkara University, Himachal Pradesh. Her research interests include institutional research strategy, academic analytics, and outcome-based project management. She is actively involved in enhancing institutional research quality, promoting innovation-driven initiatives, and supporting interdisciplinary collaboration.

Dr.R. Murugan is a Professor in the Department of Computer Science and Information Technology at JAIN (Deemed-to-be University), Bangalore. His research areas include software engineering, artificial intelligence, and computer systems optimization. He has numerous publications and actively engages in mentoring students, leading research projects, and developing innovative computing solutions.

Dr. Pooja Varma is an Associate Professor and Head of the Department of Psychology at JAIN (Deemed-to-be University), Bangalore. Her research focuses on clinical psychology, behavioral studies, and mental health interventions. Dr. Varma has published in reputed journals and actively mentors students in research projects, promoting evidence-based psychological practices and interdisciplinary collaboration in mental health studies.