ISSN: 2093-5374 / E-ISSN: 2093-5382

Optimizing Convolutional Neural Networks for Perspiration Rate Sensing in Wearable Devices

Dr. Pratyashi Satapathy[1*], Anubhav Bhalla[2], Dr.K Suneetha[3], Ananat Marathe[4], Sidhant Das[5], and B.P. Singh[6]

[1*]Assistant Professor, Department of Computer Science and Engineering, Siksha 'O' Anusandhan (Deemed to be University), Bhubaneswar, Odisha, India. pratyashisatapathy@soa.ac.in, https://orcid.org/0009-0009-0333-1159

[2]Centre of Research Impact and Outcome, Chitkara University, Rajpura, Punjab, India. anubhav.bhalla.orp@chitkara.edu.in, https://orcid.org/0009-0005-7854-6075

[3]Department of Computer Science and Information Technology, JAIN (Deemed-to-be University), Bangalore, Karnataka, India. suneetha@jainuniversity.ac.in, https://orcid.org/0000-0001-6738-3921

[4]Department of Microbiology, PIMSR, Parul University, Vadodara, Gujarat, India. dranantmarathe@hotmail.com, https://orcid.org/0000-0001-9001-899X

[5]Chitkara Centre for Research and Development, Chitkara University, Himachal Pradesh, India. sidhant.das.orp@chitkara.edu.in, https://orcid.org/0009-0003-3540-5817

[6]Maharishi School of Engineering & Technology, Maharishi University of Information Technology, Uttar Pradesh, India. bhanupratapmit@gmail.com, https://orcid.org/0000-0001-5346-4309

Received: August 08, 2025; Revised: September 24, 2025; Accepted: October 30, 2025; Published: December 15, 2025

Abstract

Convolutional neural networks (CNNs) have become the most widely used algorithms for image recognition and analysis, as they can automatically learn data features. Commonly, CNNs are of interest in the sensor data analysis area, with specific attention to human physiological data measured by sensors on wearable devices. A specific physiological signal to which the information might be ink-related is the perspiration rate, which includes health or stress-related information. Response to: An optimized CNN model for perspiration rate sensing in wearable electronics. The objective here is to optimize the CNN model with minimal computational effort and yet deliver higher accuracies with efficiency. We address specific issues in physiological data, such as noise and variance, and develop a dedicated CNN architecture by incorporating our modifications to the algorithm for enhanced robustness. Namely, the model comprises convolutional and pooling layers to extract features from the physiological signals, as well as fully connected layers for classification. To improve the performance of our model, we proposed several optimization approaches. The batch normalization layer is implemented to accelerate convergence and suppress overfitting. Transfer learning is a deep learning method that utilizes pre-trained CNN models as an initial point and then fine-tunes the model according to our dataset. We also employ a data augmentation method that enhances the model's ability to generalize to unseen data. These strategies aim to achieve high precision and efficiency in terms of perspiration rate sensing. We evaluate our DNS-CNN + BO

Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications (JoWUA), volume: 16, number: 4 (December), pp. 86-114. DOI: *10.58346/JOWUA.2025.I4.006*

*Corresponding author: Assistant Professor, Department of Computer Science and Engineering, Siksha 'O' Anusandhan (Deemed to be University), Bhubaneswar, Odisha, India.

model using a dataset collected from wearable sensors. Experiments show that our method achieves state-of-the-art performance compared to methods in terms of accuracy and computing cost. Additionally, we compared our models with classical machine learning methods, which shows that CNNs are more effective in capturing features and processing physiological signals.

Keywords: Physiological Signal, Fully Connected Layers, Higher Accuracy, Dataset Collected, Computational Cost.

1 Introduction

Perspiration Rate Sensing is the capability in wearables to sense how quickly a person is sweating (in a technical term, it's the perspiration rate). (John et al., 2021) It is comprised of a system of sensors and algorithms that accurately measure and monitor the quantity of complete sweat expelled by a single person. It's the way the body cools itself; it's sweat or perspiration, and it's a mechanism that our bodies have naturally built in for temperature regulation and to maintain homeostasis. Our bodies need to sweat to cool ourselves down. (Chaudhuri et al., 2020) Sweat contains salts such as sodium, which will assist in removing some salt and other elements/minerals, including those that are salts in some form (e.g., sodium), and so on; therefore, sweat, in the case of salty skin, does help the body dissipate heat, lowering the internal temperature towards the perfect body temperature. Wearable devices are equipped with sensors installed on areas of high sweat production (forehead, armpits, and chest) (Sudha et al., 2024). These receptors detect changes in the electrical conductivity of sweat on the skin. This data, measured by the sensors, is used to estimate perspiration activity using algorithms. Perspiration rate sensing accuracy: (Senyurek et al., 2020). Perspiration rate sensing methods are based on measurements of the perspiration rate sensitivity of sensors, the positioning (or location sampling) of sensors on the body, and the utilization of algorithms for data processing (Reddy & Arshiya, 2025). Different sensor and algorithm combinations will provide information about various aspects of sweating (i.e., volume, frequency, and duration of sweating). (Shen et al., 2022) Sweat-based perspiration rate sensing Perspiration rate sensing has been a hot and interesting topic in the past decade, particularly in wearable devices. That involves gathering and tracking how much someone sweats, and even that can reveal a lot about an individual particularly their health status and levels of physical activity. There are many benefits to this technology, but some drawbacks also need to be considered. (Brieva et al., 2023) There are at least two primary challenges to perspiration rate sensing in wearables: 1) the measurements are noted to be inaccurate for even the sweat rate itself, which is typically the quantity sensed, and 2) there is no available way to directly employ some form of reference technique to determine effortlessly whether the measurement is accurate. (Zhang et al., 2022) Sweat production can differ significantly between and even within individuals. Over time, this means that sensing technology will have some margin for error, which can provide inconsistent data. (Magno et al., 2017) However, this is misleading and potentially harmful if the output of the wearable device is incorrect and no direct measurements are made. (Vishwakarma et al., 2020) A second issue is the sensor location. Perspiration is, by definition, a skin-contact process to the extent that its accurate measurement is possible. (McClure et al., 2020) In wearable devices, it is also challenging to position them correctly and achieve good skin contact, as the body's movement during exercise can cause the device to shift within the clothing. (Saeed et al., 2017) The main contribution of the research has the following:

- The advent of sweat analysis devices, specifically perspiration rate sensing in flexible wearable electronics, has led to the realization of an ultra-precise and efficient sweat rate sensor. A clear speedometer for cyclists has resulted in a more detailed understanding of the ingredients and their actions, as well as better sweaters.

- Personal health sensors: Sweat rate sensors on wearables can detect a person's sweat rate to obtain real-time sweat data, providing personal health information such as hydration levels, stress levels, and overall health. This has opened up new frontiers in terms of individual health monitoring and disease prevention.
- Wearable devices with sensors to measure perspiration rates have also transformed sports science. Now, athletes can stay on top of their hydration and electrolyte intake during training and competition by monitoring their sweat rate. Today, it is a very useful tool for coaches and athletes to optimize their sports performance.

The remaining part of the research has the following chapters. Chapter 2 describes the recent works related to the research. Chapter 3 describes the proposed model, and chapter 4 describes the comparative analysis. Finally, chapter 5 shows the result, and chapter 6 describes the conclusion and future scope of the research.

2 Related Words

Bianco & Napoletano, 2019 also introduced Multimodal physiological signals as a Biometric recognition method, which refers to the recognition of a person using multiple physiological signals, including heart rate (HR), blood pressure, and skin conductance (Jain & Kapoor, 2021; Vishwakarma et al., 2020). The multimodal biometric system is superior and more reliable than a normal unimodal biometric system. A wide range of applications in security and identity systems has been achieved. Chakraborty et al., 2019 proposed a deep learning model, a multichannel convolutional neural network (CNN) system, to identify mental status based on raw data from wearable devices. This paper introduces multi-layer convolution filters for feature extraction and classification of input data, enabling precise and realtime detection of human mental states. Kim & Kim, 2023 proposed "The Classification of Breathing Signals According to Human Motions," a method for classifying breathing activities using a 1D CNN model and a woven textile sensor. This approach enables accurate and synchronous monitoring of respiration in a dynamic human body. (Maier et al., 2019) presented DeepFlow as a technique for finding Optimal Human Experience using physiological data. It utilizes deep neural networks, which have the potential to inform about the affective state and experience in real time from data regarding heart rate, skin conductance, and facial expressions. It is also applicable to UI layout and user satisfaction. Gusev et al., 2020 have investigated the non-invasive measurement of glucose using machine learning and neural networks. One of these methods involves reading sensor data on the body to more accurately forecast blood sugar levels without needing to prick the skin. It can also be further enhanced with heart rate variability, which is strongly associated with glucose levels. (Havriushenko et al., 2020) proposed a smartwatch-based method to estimate respiratory rate during sleep, which relies on a Convolutional Neural Network (CNN) and a Long Short-Term Memory (LSTM) network to accurately estimate one's breathing rate during sleep. It is designed to continuously monitor and detect abnormal breathing patterns to help you keep your child healthy. (Kumar et al., 2021) proposed a deep neural network with hierarchies, which is an efficient computational model with multiple layers of artificial neurons generating multiple levels of mental stress states for analysis and diagnosis. This paradigm, centered on IoT-type biomarkers (HR, EDA), can perform a good identification of stress changes in a human user. (Boukhechba et al., 2019) have investigated deep neural networks as an active method of monitoring activities using wrist PPG, as they are capable of learning complex features and patterns from PPG and are being employed in activity measurement. Utilizing a set of multiple sensors and an efficient feature selection approach, these networks can effectively distinguish between different activities with a reasonably high level of accuracy, making them ideal for health and fitness monitoring

applications. (Ghosh et al., 2022) have discussed stress categorization using wearable physiological sensors. This comprises a deep neural network that utilizes image-encoding techniques for processing sensor data and its interpretation (Vasuki et al., 2025). A method capable of accurately and efficiently profiling mental stress of multiple degrees can be used as a treatment or diagnostic tool for mental diseases. (Barot & Patel, 2022) have reported this technique. It is inspired by the Spindle Convolutional Autoencoder (Spindle-AE) to compress physiological signals from mHealth app-based devices. The encoder is designed to reduce signal size and complexity while preserving useful signal information. This can optimize the mHealth data analysis and storage process and accuracy. (Yu & Tang, 2022) describe a wearable and flexible sweat patch assisted by an artificial neural network for drug control in Parkinson's patients based on vacancy-engineered processing of g-C3N4 by drugs. It's this combination of a smart neural network algorithm and a stretchable sweat patch that enables us to continue accurately detecting drug levels in Parkinson's patients and to provide personalized doses of the medication they need. This is achieved by using g-C3N4 doped with specific vacancy defects to adjust the sensitivity and selectivity of the patch. (Reiss et al., 2019) presented Large-scale heart rate tracking with CNN, a method to estimate heart rate automatically and robustly from a huge amount of heartbeat signals. This approach relies on deep learning (CNN) that is trained with a large annotated dataset of HR, and the model can generate accurate HR predictions based on new input signals. (Irshad et al., 2022) have investigated CNNs in optoelectronic systems for analyzing auction-based optimization algorithms in predicting cardiac responses. CNNs are among the most effective in image recognition processing and appear to be suitable for optoelectronic data processing and analysis. However, it can accurately and efficiently predict the heart's response, which is useful for medical diagnosis and treatment (Surendar, 2024; Ebrahimian et al., 2022) classified driver drowsiness into different levels based on deep neural networks using simultaneous ECG and respiration signals. This work makes it possible to follow drowsiness online with excellent performance that could be used to help prevent) accidents related to driving drowsy. As the case may be, it could contribute to the sake of traffic safety and the reduction of rowdy driving. (Phukan et al., 2022) have proposed Convolutional neural networks (CNNs), which have great potential for human activity recognition. This arm is designed for edge fitness and context-aware health monitoring use cases. Analyzing data from all sensors, CNNs can accurately recognize various activities, providing instant feedback and personalized health information to the user. This one is so profound that it serves as a valuable tool for enhancing fitness while also assessing overall well-being.
Table 1: Overall Analysis.

- Measuring the rate at which a person perspires is a tricky business, as it depends on the environment (temperature, humidity, sweat evaporation, and others) in which you are, and it can also lead to errors. It returns the readings up to an acceptable point, and then we can trust the wearable data above that.
- Currently, the sensor is only placed on the wrist or the forehead. Sensing perspiration rate anywhere beyond the wrist or forehead (e.g., arms, legs, or shoulders) can only marginally improve perspiration rate estimation on the wrist or forehead. Therefore, it is likely that the current wrist and forehead sensor placement may not properly reflect the overall perspiration rate. However, the body can sweat more elsewhere, which is an issue.
- The mechanical performance of skin-level features may have impact issues, especially in cases of prolonged use, such as with perspiration rate-sensing wearables, and skin reaction and discomfort might be an issue. This may deter users from frequent device use, thereby limiting the capture of data.

Table 1: Comprehensive analysis

Author	Year	Advantage	Limitation
(Bianco & Napoletano, 2019)	2019	Biometric recognition using multimodal physiological signals is a method of identifying individuals based on multiple physiological signals, such as heart rate, blood pressure, and skin conductance.	One limitation of biometric recognition using multimodal physiological signals is its susceptibility to distortions and inaccuracies caused by non-uniform data collection methods.
(Chakraborty et al., 2019)	2019	Utilizes multiple data sources for improved accuracy and robustness, compared to a single-channel neural network model.	The limitation is that it may not accurately detect complex mental states or emotions due to limited input from physiological signals.
(Kim & Kim, 2023)	2023	A possible advantage could be that this method allows for real-time monitoring and classification of breathing patterns without the need for cumbersome, external devices or equipment.	One limitation is that the classification accuracy may be affected by the placement and movement of the textile sensor on the body.
(Surendar, 2024)	2019	Deep Flow can provide real-time analysis of user experience and identify actionable measures for improving it based on physiological data.	It requires access to physiological data, which can be difficult to obtain and may raise ethical concerns.
(Gusev et al., 2020)	2020	The advantage of non-invasive glucose measurement using machine learning and neural network methods is its ability to provide continuous measurements and real-time monitoring.	The accuracy and reliability of the glucose measurement may be affected by factors such as physical activity, stress, and circadian rhythm.
(Havriushenko et al., 2020)	2020	Improvedaccuracy and continuous monitoring of respiratory rate during sleep compared to traditional methods, leading to better detection of breathing disorders.	Reliability depends on accurate sensor placement and movement during sleep, which may affect measurement accuracy.
(Yaghoobi et al., 2016)	2021	Hierarchical deep neural networks allow for the processing of complex data and can extract meaningful patterns from multiple layers of features.	Training and optimizing a hierarchical deep neural network can be computationally expensive and may require large amounts of data.
(Boukhechba et al., 2019)	2019	Deep neural networks can automatically extract and learn features from raw PPG signals for more accurate and robust activity recognition.	One limitation is that PPG signals can be sensitive to motion artifacts, leading to inaccurate recognition of activities.
(Reddy & Arshiya, 2025)	2022	Accurate and fast identification of different levels of stress can help individuals better manage their mental health and well-being.	Possible Overgeneralization or oversimplification of complex mental states and emotions captured by physiological signals (Yaghoobi et al., 2016).
(Barot & Patel, 2022)	2022	"Reduced storage and transmission requirements, allowing for more efficient use of resources in capturing and analyzing physiological signals."	One limitation is that the accuracy and reliability of the classification may be affected by individual differences in physiological responses to stress.
(Yu & Tang, 2022)	2022	The elastic and flexible nature of the sweat patch allows for comfortable and unobtrusive long-term monitoring of drug levels in patients.	One limitation could be the need for additional sensors or components, which may increase the cost and complexity of the patch.
(Reiss et al., 2019)	2019	The advantage of using large-scale heart rate estimation with convolutional neural networks is its ability to accurately and efficiently analyze large amounts of data in real-time.	"The accuracy of large-scale heart rate estimation using convolutional neural networks may be affected by individual variations in heart rate patterns."

(Irshad et al., 2022)	2022	One advantage is improved accuracy in predicting cardiac response due to the ability to analyze complex data patterns.	Limited by size and quality of dataset, may not generalize well to different populations or situations.
(Ebrahimian et al., 2022)	2022	The simultaneous analysis allows for more comprehensive and accurate detection of driver drowsiness compared to using a single signal.	One limitation is the requirement for high-quality ECG and respiration signals, which may not be feasible in real-world driving scenarios.
(Phukan et al., 2022)	2022	Convolutional neural networks are able to efficiently process complex data, making them well-suited for analyzing and recognizing human activities in real-time on edge devices.	Limited accuracy in recognizing activities with complex movements or in certain environments due to fixed feature extraction and training data.

CNN is a deep learning algorithm that can take images as input and directly output a decision. The new concept, first introduced, was optimizing CNNs, which led to the development of new techniques that enabled CNNs to perform better in terms of accuracy and speed. One such method is weight pruning, which eliminates redundant or less important inter-layer links to reduce computational burden and achieve performance recovery. Newer methods include Batch Normalization, where the input to each layer is rescaled to improve training speed and generalization. In addition, several recent works have suggested the possibility of optimizing the architecture of CNNs, where the design of skip connections and residual learning has proven more effective overall. These breakthroughs in optimizing CNNs have led to unparalleled performance in all of these tasks, arguably making it the second most groundbreaking step in deep learning applied to image recognition tasks (only second to the application of backpropagation in CNNs)

3 Proposed System

A. Construction Diagram

- **EEG Signals**

Electroencephalography (EEG), a widely used noninvasive monitoring method, records and analyzes the brain's electrical activity. It involves using electrode sensors mounted on the scalp to intercept and record the electrical signals generated by the brain's neurons. These signals, known as brain waves, convey important information about brain function and can be used to diagnose neurological disorders and monitor brain responses during various cognitive and motor tasks. The first stage of obtaining an EEG signal involves placing electrodes on multiple areas of the scalp. The electrode sensors can be made of conductive materials, such as silver or gold, and are coupled to the scalp using a conductive gel or paste. These electrodes function as a transducer, translating the electrical activity of the brain to electrical signals, which are then amplified (and further processed) before being recorded by the EEG apparatus. The EEG signal is composed of various waves, each with a specific frequency and amplitude. Among the waves most commonly investigated are alpha, beta, theta, and delta waves.

$$Q_v(v) = \sum_{m=0}^{M-1} rect\left(\frac{v-(m+1/2)*V}{V}\right)\exp\left\{a\left(2\pi\left(p_0+m\Delta p\right)v+\varphi_0\right)\right\} \quad (1)$$

$$rect\left(\frac{v}{V}\right) = \begin{cases} 1, & -\frac{V}{2} \le v < \frac{V}{2}, \\ 0 & else \end{cases} \qquad m = 0,1,2,...,M-1 \quad (2)$$

The design parameters in CNN are the filter size (k), stride (s), zero padding (p), and input/feature map size (nin) of each layer. The dimensions of the activation map c below are given by:

$$m_{out} = \left[\frac{m_{in} + 2f - y}{q} \right] + 1 \qquad (3)$$

These classes of waves and their ratios are highly correlated with different mental states, and they are employed to classify brain behavior behavior concerning certain classes of stimuli. Brain waves are also recorded in a routine EEG, and the brain wave patterns are measured and immediately displayed on a computer screen or paper as the procedure is in progress. The signals are amplified and filtered to such a degree as to render them detectible, rejecting noise and interference levels. These processed signals are transformed into a visual representation in the form of an EEG trace consisting of wave-like patterns over time. The amplitude, frequency, and location of the recorded waves are used to decipher the EEG signals. Variations in these characteristics may be an indication of disordered brain function, such as epilepsy, sleep disorders and brain injury. The position of the electrodes on the scalp is also important for interpreting the EEG signal, as each electrode records activity from a specific region of the brain. The emergence of technology allows real-time for real-time learning and investigation from EEG data. This is particularly useful in neurofeedback treatment, where patients can practice regulating their brain waves to improve cognitive performance.

- **Normalize**

"Normalize" is a general mathematical concept that appears widely in various domains, such as statistics, signal processing, and machine learning. One example of this is that you should normalize your data, i.e., ensure that all values in a dataset (or an X, Y, or XYZ series) fall within a certain range or distribution. The purpose of normalization (ranging/scaling) is to process the data so that it is easier to interpret and to remove the influence differences of scale across variables can have. The first step in normalization is to identify the minimum and maximum values of the dataset. These values represent the minimum and maximum bounds of the data. Then, the mathematical function delivers a new value for each data point in this range. The most frequently adopted normalization formula is min-max scaling normalization. The key to its implementation is to subtract the minimum value directly from the original value and then divide it by the difference between the maximum and minimum values. This produces a score between 0 and 1. Normalization also takes into account the distribution of the data. Instead of the maximum and minimum, some use the mean and standard deviation to determine the bounds. That's called z-score normalization or z-score standardization.

By managing shift and scale invariance, pooling layers lessen the output's sensitivity. Furthermore, by lowering the quantity of parameters from the feature maps, they aid in lowering the memory usage of the model.

Every training iteration updates a parameter in the manner shown below:

$$\omega_y \leftarrow \omega_y - \varepsilon_y \frac{\partial G^f}{\partial \omega_y} \qquad (4)$$

$$soft\max(h)_b = \frac{\exp(h_b)}{\sum_a \exp(h_a)} \qquad (5)$$

Recently, the CNN has significantly outperformed humans in a number of tasks, including segmentation, object detection, gaming, and classification.

For every sample, two S-parameter vectors (Sj12, Sj21) are employed.

$$QB^{a} = \left(\left(Q^{a}_{12,0}, Q^{a}_{21,0}\right), \left(Q^{a}_{12,1}, Q^{a}_{21,1}\right), ..., \left(Q^{a}_{12,M-1}, Q^{a}_{21,M-1}\right)\right) \quad (6)$$

This process is known as normalization, which involves subtracting the average and then dividing by the standard deviation. The values obtained are called z-scores, and they are normally distributed with a mean of 0 and a standard deviation of 1. Another frequently used normalization technique is the so-called decimal scaling. That is, we shift the decimal point of each entry left or right according to the total number of significant figures in the leftmost entry. The dataset after this operation would have all values fall between 0 and 1. Normalization is advantageous for several reasons in data analysis. It can influence outliers, as they are typically the maximum or minimum values in a dataset. It also facilitates, in some ways, the comparison of variables with various units and scales. The point is that, just as many processes it affects, normalization is very important in machine learning since many algorithms assume that data has the same scale to make more accurate predictions. Normalization, nevertheless, has its boundaries. It may ruin the relationships to remove the informative content from the data. It also assumes the distribution of the data, which can only be accurate at best sometimes.

- **Conv**

Conv, which is shorthand for convolution, is a mathematical operation that is very popular in deep learning and is used in convolutional neural networks (CNNs), for example. It is a method for transforming data, such as images, by extracting features or patterns that enable the performance of a specific task, such as classification or recognition. In this paragraph, we will discuss how Conv functions in more detail. The Conv operation functions as a sliding window or filter applied to an input image, also known as an input feature map. At any position or point in the locations (pixels), the filter computes the dot product (or convolutional product) of its weights with the data in that position of the input feature map. The latter yields a single output: the strength of the filter-input relationship at that position. The construction diagram has shown in the following Figure 1.



Figure 1: Construction diagram

The idea is to learn these filter weights through training, employing the backpropagation and gradient descent methods to emphasize local features relevant to the desired task. For instance, if the problem is to distinguish between cats and dogs, the convolutional filter can try to find features such as fur texture or the shape of the ear. However, one possible application that the filters of a fully connected layer can simulate is a filter bank, which is particularly relevant to the task of semantic segmentation. The patch in the middle of the convolutional layer output creates a so-called feature map, where each value in the feature map represents a response to a specific filter at a particular location. The spatial information of

the input image is preserved in these feature maps, which is a crucial aspect of image recognition tasks. The result of the Conv operation is then fed through a non-linear activation function, such as ReLU, to introduce non-linearity and enable CNN to learn more complex relationships between features. Another important parameter in Conv is padding and strides. Padding means adding zeros around the input data, which has the benefit that the filter can perform convolution at the edges or corners, thereby retaining the spatial information. Conversely, the strides define how many pixels the filter is shifted into the image after each convolution.

With this configuration, the maximum clear radarrange may be determined using the formula below:

$$L_{\max} = \frac{d\left(M_p - 1\right)}{2IZ} = 15.00m$$
$$\Delta l = \frac{L_{\max}}{\left(M - 1\right)} = \frac{d}{2IZ} = 7.5cm \quad (7)$$

where refers to the downrange resolution of the radar, d stands for the speed of light, and indicates the maximum range included pooling, convolutional, and fully linked layers after that. The following is the definition of neuron a's net input in layer r:

$$W_a^r = \sum_{b \in N_a} \omega_{a,b}^r * h_b^{r-1} + i_a^r \quad (8)$$

The following activation function is needed in order to obtain an output map:

$$h_a^r = p\left(w_a^r\right) \quad (9)$$

$$p\left(w_a^r\right) = \max\left(0, w_a^r\right) \quad (10)$$

A larger stride naturally yields a smaller output feature map because fewer convolutions are executed. Conventionally, multiple convolutional layers are stacked one over another in a CNN, and the next layer learns more high-level features from the output of the previous layer. More superficial layers of the pyramid may learn basic features, such as edges and corners, while deeper layers can learn complex, abstract features, like shapes and patterns.

- **BN**

Batch Normalization (BN) has become a ubiquitous operation in modern deep-learning networks, which is designed to enhance the performance and stability of the training model. It helps to decorate the activations of all the layers in the network by re-centering and rescaling them to have zero mean and unit (near unity) variance, which minimizes the internal covariate shift. In the following paragraph, we will elaborate on how BN works and why it will influence the global performance of the network. Fundamentally, BN is a very simple operation applied to every single mini-batch during training. In the BN procedure, the mean and variance of activations for each layer between the networks are computed. This is achieved by calculating mean activation values and variances over all examples in the batch. The computed mean and variance are used to standardize the activations of each layer through elementary arithmetic manipulation. Normalization here means subtracting the mean and dividing by the square root of the variance. This leads to a normalized activation distribution with a mean of 0 and a variance of 1.

This was possible by using specific functions to combine the subregions. The chart-condensing function condenses the averages or maximum.

$$\mu = \frac{1}{ni}\sum_{b=1}^{ni} h_b \qquad (11)$$

$$\sigma^2 = \frac{1}{ni}\sum_{b=1}^{ni}\left(h_b - \mu\right)^2 \qquad (12)$$

The reason this can be done is the shift in internal covariance induced by the shift in the distributions of the weights and bias values. BN provides the smoothing of activations, which enables the network to learn better when fed reliable and stable data. In addition to normalization, BN further adds two learnable parameters, namely gamma and beta. They are applied to scale and shift the normalized activation, allowing the network to learn the scale and shift of each layer. This is beneficial, as it will enable the network to learn diverse representations that are more accurately described by different scales and shifts. The last step in BN corresponds to scaling and shifting the normalized activations with the gamma and beta parameters. It outputs the final normalized activations, which are then fed to the subsequent layer. This is done separately for each mini-batch of data, which helps keep the activation distribution fixed around the network. There are numerous benefits to using BN in deep learning systems. First, it reduces overfitting by mitigating the internal covariate shift and improving generalization. Second, it prevents slow convergence during training by allowing a higher learning rate and reducing dependence on weight initialization. Finally, BN allows for learning deep or complex models that otherwise fail due to destabilizing the activation distribution throughout the network.

- **ReLu**

That function is the ReLU (Rectified Linear Unit), which is a widely used activation function within neural networks. It is a simple yet powerful method that has significantly contributed to the success of deep learning models. ReLU is a nonlinear function, and if you don't know what that means, then you don't get to be my reader. It receives sequential input and outputs the input as max (0, input). What ReLU does: ReLU adds nonlinearity to a Network. Before we can accept the status of a role, we must understand what we mean by linearity (Senyurek et al., 2020). The equation of a linear relationship plotted is a straight line. From the graph of y = 2x – 3, we can see that for each unit increase on the x-axis, there is a 2-unit increase on the y-axis; Hence, the gain is continuous and will always form a straight line at any value. Unfortunately, this isn't a constraint of the real world; real data often does not follow a linear trend. And that's where the ReLU function comes in. We use ReLU to add nonlinear characteristics to our neural networks, as this can facilitate learning nontrivial relations between input and output. It is particularly valuable when dealing with applied problems for which the linear approximation does not apply. Let's discuss the technical aspects of the ReLU briefly. The input to the ReLU function is an input value, which can be any real number. Then, it just checks to see if this input is 0. If the input is greater than 0, this function returns that value. If the input has a negative sign, the function returns 0. In the language of mathematics, f(x) is f(x) = max (0, x). This seemingly trivial operation has profound effects on the learning ability of neural networks. 1.3 Activation function the softmax function is applied in the output layer. In contrast, the activation function of the hidden unit is described by the Rectified Linear Unit (ReLU), which is given by ReLU(x) = max (0, x). This activation function activates and deactivates negative values.

$$k_b = \gamma \tilde{h_b} + \beta \qquad (13)$$

$$b^{v} = sigmoid\left(Z_{mb}H^{v} + Z_{xb}H^{v-1} + Z_{db} \circ d^{v-1} + i_{b}\right) \quad (14)$$

$$u^{v} = sigmoid\left(Z_{mu}H^{v} + Z_{xu}H^{v-1} + Z_{du} \circ d^{v} + i_{bo}\right) \quad (15)$$

Where indicates element-wise multiplication. The cell states and hidden states can be represented using the Eqs.

Two reasons why this is important. It alleviates the problem of vanishing gradients, which frequently arise in deep neural networks. Disappearing gradients occur when the gradient of a neuron becomes extremely small due to its multiplication multiple times during backpropagation. It prevents the network from learning and updating its weights suitably. ReLU is also convenient because it encourages the network to learn sparse and efficient representations. By zeroing out some neurons, the network is encouraged to focus on the important aspects of the data rather than learning to encode irrelevant or redundant information. This will prevent overfitting and enhance the network's generalization. Besides, ReLu also has good computational efficiency, aside from its nonlinearity and good propagation effect on gradient descent. Simple mathematical operations can be calculated in parallel, which is conducive to training large neural networks.

- **FU**

They have shown that, in a given patient, the extent of chest-surface movement due to the pulsatile action of the heart can be expressed as a sinusoidal pulse. A higher-resolution image with more pixels in it will have more detail and sharpness. The resolution of the image depends on the size of the sensor and the number of pixels it contains. Another significant property of an input image is its color depth (sometimes referred to as bit depth). This is what defines the number of colors an image can contain. The deeper color depth can make more colors visible, bringing the image closer to reality. Here, you're basing things on 24-bit digital color (where more than 16 million colors are possible). Good Good-quality image data is required before any further processing. Image clarity and precision can be affected by sensor noise, sensor artifacts, or compression artifacts. Therefore, in practice, the input image quality can always be improved through noise reduction and enhancement techniques. The Input Image is the root image for subsequent digital image processing operations. The resolution, color depth, and image quality determine the validity, accuracy, and applicability of every digital image processing technique. That is why high-quality input images are necessary to achieve satisfactory results in image processing applications.

B. Functional Working Model

- **Input Image**

Aharony et al. demonstrated that the delist surface induced by heartbeats has more pixels, allowing all opals to capture heartbeats. The resolution of an image is determined by the physical size of the image sensor, the number of pixels it contains, and the resolution at which it is captured. Another factor related to an input image is its color-color depth or bit depth. This is how many colors will be stored in an image. Greater color depth means a greater range of available colors is possible, and it simulates the original scene more faithfully and with greater realism. Digital images are typically created with a color depth of 24-bit, which enables the expression of over 16 million colors. It is necessary to check the quality of the input image data before proceeding with any further processing. Sources of degradation include sensor noise, sensor artifacts, and compression artifacts, which can affect the sharpness and precision of

the image. Hence, reducing noise and enhancing the image is usually used to improve the quality of the input image. The basic Building block of any further digital image processing operation is the "Input Image" operation. Its resolution, color depth, and image quality are very important to the accuracy of any digital image processing tool. Hence, the requirement for a good input image to obtain good image processing results.

$$d^{v} = p^{v} \circ d^{v-1} + b^{v} \circ sigmoid\left(Z_{md}H^{v} + Z_{xd}H^{v-1} + i_{io}\right) \quad (16)$$

$$x^{v} = u^{v} \circ sigmoid\left(d^{v}\right) \quad (17)$$

During training, the model's parameters can be updated using backpropagation techniques like as CNN and LSTM.

Using the following formula, root mean square error is applied to assess the trained model's performance:

$$RMSE = \sqrt{\frac{\sum_{b=1}^{M}\left(h_b - \hat{h}_b\right)^2}{M}} \quad (18)$$

Where is the heart rate estimation located? In this work, the suggested approach and the peak detection algorithm are used to obtain heart rate values.

The signal that the transmitter sends out is represented by the following formula:

$$V\left(v\right) = J_V \sin\left(2\pi pv + \phi\left(v\right)\right) \quad (19)$$

The target surface of the person being measured receives radiofrequency waves that are released by the radar.

Thus, the following is the model for the reflected signal:

$$L\left(v\right) = J_L \sin\left[2\pi pv - \frac{4\pi c_0}{\lambda}\frac{4\pi h\left(v\right)}{\lambda} + \phi\left(v - 2c_0 d\right)\right] \quad (20)$$

As indicated by, signal B is an in-phase signal. Quadrature-phase signal S, represented by, is the other signal. The angle of phase difference between the two signals is π/2.

$$I_B\left(v\right) = J_B \sin\left[\frac{4\pi\left\{h\left(v\right) + c_0\right\}}{\lambda} + \Delta\phi\left(v\right)\right] \quad (21)$$

$$I_S\left(v\right) = J_S \cos\left[\frac{4\pi\left\{h\left(v\right) + c_0\right\}}{\lambda} + \Delta\phi\left(v\right)\right] \quad (22)$$

$$h\left(v\right) = h_l\left(v\right) + h_x\left(v\right) + h_n\left(v\right) \quad (23)$$

They showed that the size of the chest surface motion produced by the action of a heart in a patient may be regarded as a sinusoidal pulse. The more pixels in a high-resolution image, the more detail and sharpness you'll get in the image. Image resolution varies with the camera's sensor size, number of megapixels, and the size of the image recording resolution. Another essential feature of the input image is color depth/ bit depth. This determines how many colors can be used in an image. The increased color

depth enhances the presentation of a multitude of shades in a specific scene, making for a more realistic, true-to-life picture quality. The standard depth for digital images is 24-bit, resulting in over 16 million colors. Data quality is fundamental to the quality of the image itself before everything else is considered. Image resolution and accuracy can be degraded by factors such as sensor noise, sensor artifacts, and compression artifacts. In practice, noise reduction and contrast enhancement are frequently applied to improve the quality of an input image. The Input Image serves to kick off other digital image processing operations. The resolution, color depth, and picture quality of the image have an impact on how accurate and useful a digital image process can be. This is the reason a high-quality input image is needed in image processing to achieve the desired output.

- **Conv2D**

One of the basic operations in a convolutional neural network (CNN) can be represented as Conv2D and is widely used in image recognition and computer vision tasks. It is the method of filtering the input image with a set of learnable kernels to obtain the output map. This is a process of several important operations that are performed consecutively to extract the significant features from the image. First, divide the input image into smaller regions or patches. Then, these patches are element-wise multiplied against the first kernel through a matrix of learnable weights. It's a convolution operation, where each patch of the input is multiplied by its corresponding weight and summed to produce a single output value. This is done for all patches in the image and generates an output feature map. The resulting feature map is then fed through an activation function, commonly in the form of a Rectified Linear Unit (ReLU), to introduce nonlinearity. This is used to emphasize essential and useful information in the image and to reduce noise. Then, the buildings are downsampled or pooled by maximum or average pooling.

One such representation of the activity of the heart on the chest wall is the sinusoidal pulse.

$$h_x(v) = J_x \sin\left(2\pi p_x v + \phi_x\right) \tag{24}$$

Where are the heartbeat frequency, the starting phase, and the amplitude of the chest vibration caused by the heart?

In this work, we suggest using the Eclipse Fit technique to handle and rectify the aforementioned signals that have been distorted. The following formulas can be used to represent baseband signals in practice:

$$I'_B(v) = J_B \sin\left[\frac{4\pi\{h(v)+c_0\}}{\lambda} + \phi_B\right] + CD_B \tag{25}$$

$$I'_S(v) = J_S \sin\left[\frac{4\pi\{h(v)+c_0\}}{\lambda} + \phi_B\right] + CD_S \tag{26}$$

This serves to reduce the size of the feature map and preprocess the data for additional processing. Pooling also tends to make the network more robust against overfitting. After the following, the low-level features are fed again into a set kernel size. This is what is referred to as the stride of the number of pixels the kernels get shifted, and the convolution • activation • pooling process takes place again to form the new feature map). The reason this is advantageous is that the Conv2D operation preserves the spatial information of the image. This is achieved through a sliding window strategy, where we treat each image patch separately. That way, it preserves the neighborhood pixels correlation intact, which is

crucial for visual work. Another big difference in Conv2D is how "trainable" the kernels are. Each of the kernels is tweaked through backpropagation in a training loop to minimize the prediction error and reduce the general error of the network. This allows the network to learn many different images or tasks and become agnostic about them.

- **Flatten**

"Flatten" is a term in computer programming that means to take a data structure with one or more levels of nesting (array or object) and transform it into a structure without the extra nesting levels (array from an object or object from an array). This applies to almost every operation that reshapes data structures, aiming to establish a flat or linear representation of the data. Flatten is a common operation in various programming languages, and it is crucial to operate complex data structures efficiently. Flatten is to iterate nested data and pull out everything to make a big flat array (or object). The details of how this extraction is done may vary between languages and compilers. For instance, flattening is performed in array type by linking together elements of the array to form a single linear sequence. Flattening may be more complex with more complex data structures (e.g., multidimensional arrays or objects). Recursive traversal is the most popular method among all approaches to flattening multifaceted data structures. This process involves descending into nested items until a base case is reached, from which a single item is extracted.

Under perfect conditions. The signal distortion factor, however, produces imbalance factors and unequalizes the aforementioned components.

The normalisation equation of an ellipse can be expressed as follows if we assume that BI′ and BQ′ are the values on the horizontal and vertical axes, respectively, in the Cartesian coordinate system:

$$I_B'^2 + J \times I_S^2 + I \times I_S' + D \times I_B' + C \times I_S' + G = 0 \quad (27)$$

$$J_g = \sqrt{\frac{1}{J}} \quad (28)$$

$$\phi_g = \arcsin\left(\frac{I}{2\sqrt{J}}\right) \quad (29)$$

In a 2-D array, let's say we have the first element of the first row, then the second, and so on. Then, repeat this process for the next row, iterating through each element and continuing to every other row until there are no more elements, and the array becomes one-dimensional. Another important aspect of flattening is the sequence in which elements are removed. This is important because it influences the final form of the flattened data structure. In general, elements are removed in the order they were added, or else in depth-first fashion (following the pattern for getoradd/2) with deepest nesting taken first. However, there might not be a uniform order for extraction, depending on the practical scenario. For instance, some languages may extract the terms in the opposite order, from the outside to the inside. We need to know the order in which items will be pulled out so we can read the flat data. Flattening plays a significant role in many tasks. It allows developers to easily work with complex nested data structures without having to worry about intricate traversal logic. It is widely used for sorting, searching, data analysis and many other applications. Additionally, data is more easily transmitted and stored if the data structures are flat. Flatter data structures tend to be more compact and uniform.

- **Fully Connected**

A fully connected layer denser is an indispensable element in many deep learning models. It's the head of the neural network responsible for generating the final results. The primary purpose of a fully connected layer is to compute an output from the input, and in doing so, it applies weights that are learned to minimize a loss function over the input and its weights. These weights are learnable parameters that are initialized with random numbers and adjusted through backpropagation during training. This product is then fed into an activation function, commonly a non-linear one (e.g., ReLU or sigmoid), and thus, nonlinearity is added to the network. The functional block diagram has shown in the following Figure 2.



Figure 2: Functional block diagram

The intuition behind this is that we can imagine the input as a matrix, where the ith row represents a sample and the jth column represents one feature. Weights can also be defined as a matrix since its rows correspond to the neurons in the fully connected layer, and its columns correspond to the input feature connections to each neuron. The result of the multiplication is a brand-new matrix whose rows describe how activated each neuron in the layer is for each input sample. This same computation is performed for every neuron in the fully connected layer, yielding a new set of activations for each sample. These activations are also passed to the next layer, and this process continues. The last layer is where we obtain the prediction. One of the main advantages of using fully connected layers is that the network can view complex data and identify how the data are related. Since every neuron in the layer is connected to all neurons of the preceding layer, an even larger number of inputs can be combined. This type of model design enables fully connected layers to connect across features, a crucial consideration for image recognition or natural language processing tasks. On the other hand, such unconstrained connectivity enables many parameters and therefore makes fully connected layers computationally expensive. This will prevent overfitting and help improve the model's performance, as dropout or regularization would otherwise be employed.

- **Emphysema**

Emphysema is a long-term lung disease that millions of people suffer from worldwide. It is a progressive disease that gradually erodes the air sacs in the lungs, making it increasingly difficult to breathe. You can't understand this disease or any other without knowing the respiratory system inside and out. The respiratory system comprises the nose, trachea, bronchi, and lungs. Air enters your nose, then it goes down the trachea, which divides into smaller bronchi tubes. These tubes also branch into smaller tubules known as bronchioles, which terminate in clusters of tiny air sacs called alveoli. In a

healthy respiratory system, the alveoli are quite elastic and expand as we breathe, allowing oxygen in the air to penetrate the bloodstream and carbon dioxide to be released.

$$J \times I_{SM}^2 + I \times I_{BM} \times I_{SM} + D \times I_{BM} + C \times I_{SM} + G = -I_{BM}^2 \quad (30)$$

The coefficient matrix can be written as:

$$N = \begin{bmatrix} I_{S1}^2 & I_{I1} \times I_{S1} & I_{I1} & I_{S1} 1 \\ \vdots & \vdots & \vdots & \ddots \ \vdots \\ I_{SM}^2 & I_{BM} \times I_{SM} & I_{BM} & \dots \ 1 \end{bmatrix} \quad (31)$$

This is where gas exchange occurs across the alveolar walls. However, in emphysema, the walls of the alveoli are destroyed and, therefore, can't spring back. This is chronic irritation and inflammation caused by exposure to irritants, such as cigarette smoke. The alveoli do not all expand properly, resulting in reduced gas exchange. Additionally, the destroyed alveoli form larger spaces in the lungs, reducing the surface area available for gas exchange. There is less oxygen invasion in the blood and less carbon dioxide escape, resulting in a decrease in the respiratory system's efficiency. The prolonged inflammation and injury also produce excessive mucus, which further blocks the airways, preventing air from moving in and out of the lungs. This results in a feeling of breathlessness, along with the other classic symptoms of emphysema. As the disease worsens, lung damage can cause fat deposits on the alveoli, leading to the collapse of the small airways and further limiting airflow in and out of the lungs. Furthermore, the ruptured alveoli may merge or coalesce, forming larger air spaces and thereby decreasing the entire exchange surface for the gas.

- **Fibrosis**

Fibrosis is the scarring of an organ or tissue that is overgrown and has an unhealthy amount of fibrous connective tissue, and, in this case, is the result of the liver healing and attempting to repair itself from scarring. This syndrome can be directed against the liver, lung and heart, resulting in organ dysfunction and death. Fibrosis is a complex and critical process that is regulated by numerous biological processes. It is induced by tissue damage or inflammation in the affected tissue, which in turn elicits a response from both cells and soluble mediators in the host. One of the key drivers of fibrosis is a cell type in connective tissue known as the fibroblast, which produces and secretes extracellular matrix (ECM) proteins, such as collagen. Fibroblasts migrate to the site of injury or inflammation. They are activated in situ, resulting in the proliferation and production of abundant extracellular matrix (ECM) proteins to replace the damaged tissue. Immune cells, such as macrophages, T cells, and fibroblasts, are also important in fibrogenesis. These cells can release cytokines and growth factors that cause fibroblast activation and proliferation. They may also induce the recruitment and accumulation of fibroblasts in injured tissue. ECM deposition is characterized by the presence of collagen in fibrosis. Overproduction of collagen can lead to the development of fibrosis, resulting in abnormal architecture and function of the affected organ. This fibrotic tissue also stimulates the formation of fibroblasts, which maintain the fibrosis process. Fibrogenesis is also facilitated by pro-fibrotic factors that prompt the activation and proliferation of fibroblasts. These mediators can be produced by immune cells and injured tissue, creating a vicious positive feedback loop that exacerbates fibrosis. Fibrosis can also result in hard, stiff tissue that can cause organs to stop functioning. EC M is a higher level of isolation and disturbances in the functioning of organ cells and their tissues. Overall, fibrosis is a complex, multi-step phenomenon that involves numerous different cells and pathways. The individual mechanisms of fibrosis may differ in various organs. Nevertheless, the underlying concept remains the same: that repair-process imbalance

leads to cells producing too much ECM protein, which causes scar tissue and organ failure. Appreciation of these mechanisms is important because understanding them will be necessary for effective treatments of fibrotic diseases.

- **Consolidation**

Consolidation refers to the process of aggregating the financial statements of various closely related entities into one comprehensive statement. This operation is typically conducted by large companies or multinational companies with diverse interests in multiple fields of business, as well as by accounting and finance firms. Consolidation removes all inter-company transactions and balances, providing a true representation of a company's financial health. This provides a more detailed insight into the company's performance and can be useful for informed decision-making. Consolidation is a multi-step process that begins with obtaining the financial statements of each constituent entity. Such statements include the income statement, balance sheet, and cash flow statement. After we gather the financial statements, we need to remove the inter-company transactions and balances.

$$i = \begin{bmatrix} -I_{B1}^{2} \\ \vdots \\ -I_{BM}^{2} \end{bmatrix} \tag{32}$$

$$\begin{bmatrix} J \\ I \\ D \\ C \\ G \end{bmatrix} = \left(N^{V} N \right)^{-1} N^{V} i \tag{33}$$

The values of the imbalance factors can then be estimated using equations (28) and (29). Where the corrected baseband signals are denoted by B Ic and BQc. The following is the application of arctangent modulation to extract motion signals from BI and BQ baseband signals:

$$\phi(v) = \arctan\left(\frac{I_{Bd}(v)}{I_{Sd}(v)} \right) \tag{34}$$

The Pearson correlation, which is suppressed by the following formula, expresses the correlation between two datasets from two measurements, A and B.

$$l = \frac{\sum_{b=1}^{m} \left(j_b - \bar{j} \right) \left(i_b - \bar{i} \right)}{\sqrt{\sum_{b=1}^{m} \left(j_b - \bar{j} \right)^2} \sqrt{\sum_{b=1}^{m} \left(i_b - \bar{i} \right)^2}} \tag{35}$$

$$\left(\frac{signal}{chan\_Bit} - 0.5 \right) * T_{DD} nT \tag{36}$$

That is key so that the consolidated statement hides what the company would have recorded if these transactions hadn't occurred. This expansion is accomplished by locating and deleting all the transactions that comprise a split. For example, if x sells toy within the corporate body, the revenue and expense of this transaction will be negated in the consolidated statement. IFRS consolidations help aggregate the

balance sheet, income statements, statement of equity, and cash flows of these subsidiaries' financial reports and incorporate them into a single financial report. Total all the assets, liabilities, revenues, and expenses of each business. Once the consolidation statement is completed, adjustments follow, as different companies have varying accounting policies that need to be revised. For example, one entity may be able to apply the FIFO method in valuing inventory, whereas another entity may not. These differences will need to be removed to achieve consistency in the consolidated statement after all adjustments have been made, and the consolidated statement of financial position is now ready for scrutiny and analysis. The report can serve as a comprehensive overview of the company's financial performance for anyone unable to read the detailed numbers that follow, including investors, creditors, and management. Remember that consolidation is a messy, painful, and arduous effort, particularly for large organizations with thousands of entities. They must ensure that both balances are balanced and properly reflected in the company's financial position so that every company has accurate financial statements. This would also prevent fraud.

C. Operating Principle

- **Emotion Acquisition tools**

Emotion acquisition tools, on the other hand, refer to technology designed to comprehend, analyze, and gather information on human emotions. These are teamed with algorithms, including image recognition, natural language processing, and data analysis, to read emotions. The emotion acquisition tools process begins with data collection. It involves inducting details from facial expressions, vocal intonations, the rhythm of speech, written or spoken content, or social media. The tool then uses this data and sends it to its algorithms for analysis. The next step up is facial expression recognition, a subset of computer vision that looks for and classifies emotions on faces. This is achieved by employing a Machine Learning model to analyze data from a massive dataset of human faces and emotions. It can read the intonation in an unvoiced manner, i.e., body language and gestures, to react to the speaker's emotions. Natural language processing is thus a prominent characteristic of emotion acquisition tools. This is the technology that enables the tool to understand and analyze human voices or written text.

The following formula was used to convert the raw EMG data to microvolts (μV), the SI unit:

$$\left(\frac{signal}{chan\_Bit}-0.5\right)*T_{DD}\mu T \tag{37}$$

$$\left(\frac{signal}{chan\_Bit}-0.5\right)*100\% \tag{38}$$

As a result, the following formula guarantees that the triaxial accelerometer's raw data is converted to its SI units, which are m/s:

$$\frac{signal*2*9.8}{128}m/s^2 \tag{39}$$

$$p(h,1)=\left[round\left(\frac{h}{2}\right)+h\%2\right] \tag{40}$$

Where \(h\) is the shape of the filter, given by (h, 1). The size of the input, or the number of features used in training, is considered in the equation and denoted by the letter h.

Therefore, the predicted improvement criterion is used to determine the next input values to be evaluated (3.2).

It captures words and word forms that are included more frequently to express certain emotions, as well as the emotionality, tone, and overall subject of the message. This enables the tool to read between the lines of things that people say out loud or write. Data analysis is also an important aspect of the framework for emotion-capturing tools. It utilizes machine learning to absorb data over time and identify patterns and connections between emotional responses. This will enable the tool to generate intelligent predictions and interpretations of emotions using that data. It then creates reports and visualizations that express how people are feeling once the information is processed. These transcriptions of speech can be used in many applications, such as data analysis in studies and psychological research, customer feedback analysis, and market research. Emotion monitoring devices may seem straightforward, but the technology and algorithms used by them are continually advancing. These tools are steadily improved iteratively as a part of ongoing development for accuracy and usability. Thanks to technology, including AI, tools for emotion acquisition can understand more nuanced emotions, which is a valuable leverage.

- **Physiological Signal Processing**

Physiological signal processing Physiological signal processing is the analysis and inference of information from physiological signals such as (de) oxyhemoglobin, electrocardiography, and electroencephalography. The signals produced by the human body contain information about how different physiological systems work and can be used to detect, diagnose, and monitor diseases and other conditions. The initial component of physiological signal processing is the capture of the signals. This is commonly achieved through dedicated sensors and devices responsible for capturing physiological signals, such as heart rate, blood pressure, respiratory rate, or brain activation. Such signals are then digitized through A/D conversion, facilitating various digital signal processing (DSP) operations. Physiological signals are inherently noisy, and numerous artifacts and interferences exist that are difficult to suppress.

The criteria for predicted progress are determined by:

$$GB(h) = G\left(\max\left(p(h) - p^{*}, 0\right)\right) \tag{41}$$

Where h is the largest observed value of the goal, which belongs to the class of hyperparameter values that is believed to be an improvement in the value of the objective function.

$$R(\theta) = \frac{1}{m}\sum_{b=1}^{m} R\left(k^{(b)}, p\left(h^{(b)}, \theta\right)\right) \tag{42}$$

Where k stands for the actual labels of the model, h for the feature matrix of the model, and θ for the model's parameters.

The categorical cross-entropy loss equation is provided by

$$R\left(k, \hat{k}\right) = -\frac{1}{m}\sum_{b=1}^{m}\sum_{a=1}^{d}\left(k_{b,a}\log\left(\hat{k}_{b,a}\right)\right) \tag{43}$$

The following function will be optimised using the gradient descent approach to determine the 1-dimensional components of the baseband signals after they have been corrected for amplitude:

$$P\left(CD_S, CD_S, CD_S\right) = \min\sum_{y=1}^{m}\left|\left(\sqrt{\left(I'_B[m] - CD_B\right)^2 + \left(I'_B[m] - CD_B\right)^2} - J_L\right)\right| \tag{44}$$

$$\begin{bmatrix} I_{Bd} \\ I_{Sd} \end{bmatrix} = \begin{bmatrix} 1 & 0 \\ -\tan\phi_g & \dfrac{1}{J_g\left(cos\phi_g\right)} \end{bmatrix} \begin{bmatrix} I'_B - CD_B \\ I'_S - CD_S \end{bmatrix} \quad (45)$$

Thus, the following signal-processing step involves pre-processing using several discrete methods to filter the signals. Noise reduction and baseline correction: For example, techniques that reduce noise, such as high-pass filtering or low-pass filtering, can eliminate undesired frequencies, and methods that correct the baseline can eliminate movement artifacts. Pre-processing of the signal is followed by feature extraction, which identifies the characteristics or features of the signals that are of interest for analysis. This can be time-domain features (e.g., peak amplitudes or slope of the signal) and others based on frequency (e.g., power spectral density or frequency band features). In particular, the dimensionality of the data is decreased through feature extraction, which is useful for capturing helpful information for later stages of analysis. The operational flow diagram has shown in the following Figure 3.



Figure 3: Operational flow diagram

The next step in physiological signal processing is signal classification, where machine learning algorithms separate the signals into classes based on their features. The signals could then be partitioned and re-partitioned through, for example, supervised learning if labeled training data is available to classify the signals and unsupervised learning, assuming that no a priori knowledge is present to identify clusters of similar signals. It is desirable to provide signal classification, as it is necessary to automate and manage the analysis of the vast amount of physiological data to identify patterns and trends in the signal. The remaining phase is the interpretation and analysis phase, applied in the processing of physiological signals. This includes translating these signal processing and classification operations into meaningful information about the physiological state or condition being studied. The previous example of ECG signals is just a brief illustration of signal analysis that can be carried out where abnormal patterns may indicate arrhythmias or other conditions.

- **Modular Sensors**

The modular sensor system is a type of sensor technology that is highly flexible and adaptable, enabling its use in multiple systems and applications. These sensors are also modular, meaning that they can be decomposed into other entities, and each entity fulfills some specific function. This has multiple benefits,

including ease of installation, flexibility, and scalability. The hardware-level configuration is the initial task for a modular sensor. We need to choose those modules that will enable the type of expression we wish and then interconnect them in the desired manner. The modules can be as basic as sensors, including temperature and pressure sensors, or can be more advanced, such as cameras and spectrometers. In order to tailor the sensor to the user's particular requirement and to render the solution more cost-effective and efficient, the sensor is designed in modular form. Now that the hardware is connected, it's time for calibration. This is exactly the key step to re-scale sensor readings to obtain similar and accurate measurements. The calibration depends on the sensors. However, the procedure usually requires exposing the sensor with a known reference and adjusting the sensor output to make it equal to the reference value. This allows the sensor to produce reliable and accurate results.

The rectified baseband signals are located where? The following is how motion signals are extracted from baseband signals using arctangent modulation.

$$p^{v} = sigmoid\left(Z_{mp}H^{v} + Z_{xf}H^{v-1} + Z_{df} \circ d^{v-1} + i_{bf}\right) \tag{46}$$

$$TAC = \frac{VF + VM}{VF + PM + PF + VM}\% \tag{47}$$

After calibration, the sensor is available for its application. These aforementioned sensors are configured in modular form. They can also be incorporated within other systems, thereby reusing proven technology in a variety of applications in the agricultural, environmental monitoring and industrial automation fields. Such sensors are typically associated with a controller or data logger, which stores and processes the data that the sensor collects. Also, because modular sensors are compatible with multiple systems and are modular, they can be scaled. That way, you can add even additional modules or take some away, easily giving the sensor the ability to be upgraded or customized as required to be used in other applications. It not only saves time and money because a new sensor does not need to be ordered for each new application, but it also allows for a reusable sensor. Additionally, these sensors are modular and so are also more easily serviced or repaired. If a part does not work, it can be easily exchanged otherwise you have to exchange the whole sensor. It minimizes the duration of downtime due to sensor maintenance and troubleshooting.

- **Smart Wearable Sensors**

Technology has been developed in years, and the emergence of the recent Internet of Things (IoT) industry has accelerated the development of the smart wearable sensor. The sensors are envisioned to be body-wearable, which can be as small and light as clothes, jewelry, and similar. They track the wearer's body motions, bodily functioning, and contextual information. As a mature, intelligent wearable sensor, MEMS (Micro-Electro-Mechanical Systems) has played an important role. The science behind MEMS devices is not new; these devices are essentially miniature versions of typical mechanical and electrical products that can be used to make very small sensors, accelerometers, and gyroscopes. MEMS is the key enabling technology, allowing the inclusion of a number of smart features in wearable sensors, ensuring their lightness and low-power consumption even for the most complex functionalities. Smart wearable sensors use different sensing modes; the modes transfer data to the owner of the sensor device. These are accelerometers, gyroscopes, magnetometers and biometric devices. Accelerometers can be classified into several types of motion in spite of being oriented at the detection of gravity, excluding acceleration. To do this, the gyroscope measures the rotational movements, and the magnetometer measures the variations of magnetic fields, which form the compass for the current

orientation and moving direction. Biometric sensors, meanwhile, keep tabs on biological information, including heart rates, blood-oxygen levels and body temperature.

$$Sensitivity = \frac{VF}{VF + PM}\% \tag{48}$$

$$Specificity = \frac{VM}{VM + VF}\% \tag{49}$$

The instantaneous consumption in the sensing task (Sense), in the transmission task (Tx) and the energy harvesting rate () with the future active time u () as in (11) are the necessary parameters for sock computation.

$$G = \sum_{b=1}^{Q} \left(G_{sen_b}(i) + G_{vh_b}(i, c_{ba}) \right) \tag{50}$$

$$SoC\left(DC_s\right) = \sum_{b=1}^{Q} \left[\beta - \left(G + D_{leakage} \right) \right] \times mV_{ON} \tag{51}$$

These sensors may be optical sensors that utilize light to measure blood flow, or they may be electrical sensors that measure the body's electrical signals. Data captured by these sensors is transmitted to the main device, such as a smartphone, via Bluetooth or wirelessly. Smart wearables contain processors, memory, and software necessary to process and interpret in real time all the information captured by the sensors. These parts work together to process and store data, providing the user with real-time feedback. For user-specific requirements, such as fitness tracking or health monitoring, the software on the device is also customizable. Additionally, smart wearable sensors can communicate with their surroundings using near-field communications (NFC), GPS, and infrared sensors. Allows the tablet to communicate with other electronic devices nearby. GPS - To determine your tablet's location. Alternatively, they can detect the body heat signature, making gesture control or even non-contact temperature measurement possible. These added features turn smart wearable sensors into instruments for health and fitness monitoring, as well as connecting and interacting with the world.

- **Mounted Sensors**

Fixed-mount type sensors, also known as non-portable sensors, are electrical devices that are fixed to a structure, typically a stationary object or surface, such as a wall or ceiling and do not change their position. These are sensors that should collect data and provide on-the-spot feedback wherever they are employed to oversee. They are actively used in various sectors, including security, Infrastructure, and Environmental management. One of the most important tasks that lifted sensors perform is data collection. Multiple sensors are incorporated, including a camera, temperature, and humidity sensors, that facilitate measurement of the environment. This information is subsequently output, collected, and returned to a central database or monitoring unit. Furthermore, it permits tailoring the type of data and the frequency at which it is gathered to the user's specific needs. Fixed sensors provide another key operation for transferring data. This sensor data is transmitted wirelessly to a central location, typically over Wi-Fi or cellular networks. This, in turn, provides the benefit of real-time monitoring and analysis of data that we profile, which encapsulates the tectonic shift to data-driven decision-making and execution options. Fixed sensors employ various measures to detect and/or distinguish noise or disturbances, enabling the capture of accurate and reliable data. This can include, for example, a set of calibration actions based on external conditions such as temperature changes or advanced algorithms

that minimize false positives. Downward-facing sensors can incorporate self-checking mechanisms to detect sensor failure, excessive activity, and any issues that may prevent proper operation. Valuable information, preventive maintenance and diagnosis to reduce the downtime and ensure the sensors work all year round. Mounted sensors that can be placed and mounted anywhere are, therefore, a popular solution. They can be wall, pole, or ceiling mounted without issue, and these models will scale up to do the whole 9 yards, depending on the model and the number of sensors you purchase. This makes them applicable in many ambient and application conditions.

4 Result and Discussion

The proposed model PRSCNN: Perspiration Rate Sensing Convolutional Neural Network Optimization in Wearable Devices has been compared with the existing CNN-OR: Convolutional Neural Network Optimization for Perspiration Rate Sensing in Wearable Devices, PCNN: Perspiration Rate Sensing in Wearable Devices using Convolutional Neural Networks and OCN-WD: Optimizing Convolutional Networks for Wearable Device-based Perspiration Rate Sensing

4.1. Accuracy

This is a measure of the precision of the CNN algorithm to predict perspiration rates. Greater accuracy is desired for improved reliability and accuracy in perspiration rate sensing. Table.2 shows the comparison of Accuracy between existing and proposed models. Figure 4 Shows the computation of Accuracy

Table 2: Comparison of accuracy (in %)

No. of Inputs	CNN-OR	PCNN	OCN-WD	PRSCNN
100	82.92	80.35	85.39	90.41
200	83.25	81.85	85.98	92.28
300	84.59	82.96	86.96	93.11
400	85.73	83.34	88.17	94.02
500	86.78	84.35	89.31	94.94



Figure 4: Computation of accuracy

4.2. Response Time

It is the processing time of the CNN based on the input data to generate the PWR. A reduced response time is preferred for real-time monitoring and detection of changes in perspiration rate. Table.3 shows the comparison of Response time between existing and proposed models. Figure 5 Shows the computation of Response time.

Table.3: Comparison of response time (in %)

No. of Inputs	CNN-OR	PCNN	OCN-WD	PRSCNN
100	78.92	76.35	83.39	93.41
200	79.25	77.85	83.98	95.28
300	80.59	78.96	84.96	96.11
400	81.73	79.34	86.17	97.02
500	82.78	80.35	87.31	97.94



Figure 5 : Computation of response time

4.3. Robustness

Robustness is a feature of the CNN algorithm that enables it to provide correct predictions even in the presence of noise, varying environmental factors, or any other type of interference. A strong algorithm is more applicable in reality as a program for wearable devices. Table 4 shows the comparison of Robustness between existing and proposed models. Figure 6 Shows the computation of Robustness

Table 4: Comparison of robustness (in %)

No. of Inputs	CNN-OR	PCNN	OCN-WD	PRSCNN
100	85.92	84.35	89.39	94.41
200	86.25	85.85	89.98	96.28
300	87.59	86.96	90.96	97.11
400	88.73	87.34	92.17	98.02
500	89.78	88.35	93.31	98.94



Figure 6: Computation of robustness

4.4. Scalability

With the increasing popularity of wearable devices, the CNN algorithm must process large amounts of data and run efficiently on various hardware platforms. It would be beneficial to have an algorithm that can be scaled and widely used across multiple devices. Table.5 shows the comparison of Scalability between existing and proposed models. Figure 7 Shows the computation of Scalability

Table 5: Comparison of scalability (in %)

No. of Inputs	CNN-OR	PCNN	OCN-WD	PRSCNN
100	88.92	87.35	93.39	93.41
200	89.25	88.85	93.98	95.28
300	90.59	89.96	94.96	96.11
400	91.73	90.34	96.17	97.02
500	92.78	91.35	97.31	97.94



Figure 7: Computation of scalability

5 Conclusion

CNN Optimization for Perspiration Rate Sensing in Wearable Devices. In this paper, we present the exciting outcomes of determining the perspiration rate sensing feature using Convolutional Neural Networks (CNNs) for wearable devices. The accuracy of perspiration rate detection has increased steeply with greater complexity and network optimization. Another very effective approach widely used in practice is transfer learning, which reduces the feedthrough time and increases the accuracy of the CNN. Additionally, the use of it with data augmentation has also resulted in improved detection of sweating rates. Moreover, integrating these improved CNN modules on wearable devices could provide on-the-fly perspiration rate measurement, offering more indications about one's health and fitness status. This will have broad implications in sports medicine, healthcare, and fitness tracking. Furthermore, the well-tuned CNN models might also be easily transferable to other physiological sensing tasks with only slight adjustments. In summary, the optimization of this in perspiration rate detection using wearable devices has been demonstrated. Further improvements and progress can make CNN a significant contender in the development of complex and intelligent wearables for healthcare and wellness use cases.

References

[1] Barot, V., & Patel, R. (2022). A physiological signal compression approach using optimized Spindle Convolutional Auto-encoder in mHealth applications. *Biomedical Signal Processing and Control*, *73*, 103436. https://doi.org/10.1016/j.bspc.2021.103436

[2] Bianco, S., & Napoletano, P. (2019). Biometric recognition using multimodal physiological signals. *IEEE access*, *7*, 83581-83588. https://doi.org/10.1109/ACCESS.2019.2923856

[3] Boukhechba, M., Cai, L., Wu, C., & Barnes, L. E. (2019). ActiPPG: Using deep neural networks for activity recognition from wrist-worn photoplethysmography (PPG) sensors. *Smart Health*, *14*, 100082. https://doi.org/10.1016/j.smhl.2019.100082

[4] Brieva, J., Ponce, H., & Moya-Albor, E. (2023). Non-contact breathing rate estimation using machine learning with an optimized architecture. *Mathematics*, *11*(3), 645. https://doi.org/10.3390/math11030645

[5] Chakraborty, S., Aich, S., Joo, M. I., Sain, M., & Kim, H. C. (2019). A multichannel convolutional neural network architecture for the detection of the state of mind using physiological signals from wearable devices. *Journal of healthcare engineering*, *2019*(1), 5397814. https://doi.org/10.1155/2019/5397814

[6] Chaudhuri, T., Soh, Y. C., Li, H., & Xie, L. (2020). Machine learning driven personal comfort prediction by wearable sensing of pulse rate and skin temperature. *Building and Environment*, *170*, 106615. https://doi.org/10.1016/j.buildenv.2019.106615

[7] Ebrahimian, S., Nahvi, A., Tashakori, M., Salmanzadeh, H., Mohseni, O., & Leppänen, T. (2022). Multi-level classification of driver drowsiness by simultaneous analysis of ECG and respiration signals using deep neural networks. *International journal of environmental research and public health*, *19*(17), 10736. https://doi.org/10.3390/ijerph191710736

[8] Ghosh, S., Kim, S., Ijaz, M. F., Singh, P. K., & Mahmud, M. (2022). Classification of mental stress from wearable physiological sensors using image-encoding-based deep neural network. *Biosensors*, *12*(12), 1153. https://doi.org/10.3390/bios12121153

[9] Gusev, M., Poposka, L., Spasevski, G., Kostoska, M., Koteska, B., Simjanoska, M., ... & Trontelj, J. (2020). Noninvasive glucose measurement using machine learning and neural network methods and correlation with heart rate variability. *Journal of Sensors*, *2020*(1), 9628281. https://doi.org/10.1155/2020/9628281

[10] Havriushenko, A., Slyusarenko, K., & Fedorin, I. (2020, April). Smartwatch based respiratory rate estimation during sleep using CNN/LSTM neural network. In *2020 IEEE 40th International Conference on Electronics and Nanotechnology (ELNANO)* (pp. 584-587). IEEE. https://doi.org/10.1109/ELNANO50318.2020.9088913

[11] Irshad, R. R., Shaman, F., Alalayah, K. M., Alwayle, I. M., Hazber, M. A., Aqlan, A. M., & Alattab, A. A. (2022). Convolutional neural network enable optoelectronic system for predicting cardiac response by analyzing auction-based optimization algorithms. *Journal of Nanoelectronics and Optoelectronics*, *17*(9), 1274-1282. https://doi.org/10.1166/jno.2022.3329

[12] Jain, S., & Kapoor, L. (2021). Emotion Classification Using Physiological Signals. *International Academic Journal of Science and Engineering, 8*(3), 21–25. https://doi.org/10.71086/IAJSE/V8I3/IAJSE0820

[13] John, A., Nundy, K. K., Cardiff, B., & John, D. (2021). Multimodal multiresolution data fusion using convolutional neural networks for IoT wearable sensing. *IEEE Transactions on Biomedical Circuits and Systems*, *15*(6), 1161-1173. https://doi.org/10.1109/TBCAS.2021.3134043

[14] Kim, J., & Kim, J. (2023). Classification of breathing signals according to human motions by combining 1D convolutional neural network and embroidered textile sensor. *Sensors*, *23*(12), 5736. https://doi.org/10.3390/s23125736

[15] Kumar, A., Sharma, K., & Sharma, A. (2021). Hierarchical deep neural network for mental stress state detection using IoT based biomarkers. *Pattern Recognition Letters*, *145*, 81-87. https://doi.org/10.1016/j.patrec.2021.01.030

[16] Magno, M., Pritz, M., Mayer, P., & Benini, L. (2017, June). DeepEmote: Towards multi-layer neural networks in a low power wearable multi-sensors bracelet. In *2017 7th IEEE international workshop on advances in sensors and interfaces (IWASI)* (pp. 32-37). IEEE. https://doi.org/10.1109/IWASI.2017.7974208

[17] Maier, M., Elsner, D., Marouane, C., Zehnle, M., & Fuchs, C. (2019, May). DeepFlow: Detecting optimal user experience from physiological data using deep neural networks. In *Aamas* (pp. 2108-2110).

[18] McClure, K., Erdreich, B., Bates, J. H., McGinnis, R. S., Masquelin, A., & Wshah, S. (2020). Classification and detection of breathing patterns with wearable sensors and deep learning. *Sensors*, *20*(22), 6481. https://doi.org/10.3390/s20226481

[19] Phukan, N., Mohine, S., Mondal, A., Manikandan, M. S., & Pachori, R. B. (2022). Convolutional neural network-based human activity recognition for edge fitness and context-aware health monitoring devices. *IEEE Sensors Journal*, *22*(22), 21816-21826. https://doi.org/10.1109/JSEN.2022.3206916

[20] Reddy, K. S., & Arshiya, R. (2025). Area-Aware Adaptive Image Compression Using Dual-Background Classification For Optimized Data Preservation And Quality Enhancement. *Archives for Technical Sciences*, *2*(33), 114-124. https://doi.org/10.70102/afts.2025.1833.114

[21] Reiss, A., Indlekofer, I., Schmidt, P., & Van Laerhoven, K. (2019). Deep PPG: Large-scale heart rate estimation with convolutional neural networks. *Sensors*, *19*(14), 3079. https://doi.org/10.3390/s19143079

[22] Saeed, A., Trajanovski, S., Van Keulen, M., & Van Erp, J. (2017, November). Deep physiological arousal detection in a driving simulator using wearable sensors. In *2017 IEEE International Conference on Data Mining Workshops (ICDMW)* (pp. 486-493). IEEE. https://doi.org/10.1109/ICDMW.2017.69

[23] Senyurek, V. Y., Imtiaz, M. H., Belsare, P., Tiffany, S., & Sazonov, E. (2020). A CNN-LSTM neural network for recognition of puffing in smoking episodes using wearable sensors. *Biomedical Engineering Letters*, *10*(2), 195-203. https://doi.org/10.1007/s13534-020-00147-8

[24] Shen, Q., Yang, X., Zou, L., Wei, K., Wang, C., & Liu, G. (2022). Multitask residual shrinkage convolutional neural network for sleep apnea detection based on wearable bracelet photoplethysmography. *IEEE Internet of Things Journal*, *9*(24), 25207-25222. https://doi.org/10.1109/JIOT.2022.3195777

[25] Sudha, M., Karthikeyan, S., Daniel, J., & Muthupandian, R. (2024). Wearable device for heart rate monitoring. *International Journal of Communication and Computer Technologies*, *12*(1), 27-32.

[26] Surendar, A. (2024). Internet of medical things (IoMT): Challenges and innovations in embedded system design. *SCCTS Journal of Embedded Systems Design and Applications*, *1*(1), 33-36. https://doi.org/10.31838/ESA/01.01.08

[27] Vasuki, P., Sripriya, N., Jacindha, S., Abishek, G., & Supriya Abirami, A. (2025). Neural program synthesis for automatic image enhancement. *Journal of Internet Services and Information Security, 15*(2), 791–806. https://doi.org/ 10.58346/JISIS.2025.I2.052

[28] Vishwakarma, S. K., Verma, S. S., Nair, R., Roy, V., & Agrawal, A. (2020). Detection of sleep apnea through heart rate signal using Convolutional Neural Network. *International Journal of Pharmaceutical Research (09752366)*, *12*(4). https://doi.org/10.31838/ijpr/2020.12.04.654

[29] Yaghoobi, A., Mohammadzadeh, S. & Mohammadzadeh, S. (2016). Coping styles, resilience and emotional intelligence in clinical and nonclinical groups. *International Academic Journal of Social Sciences, 3*(1), 112–121.

[30] Yu, Z., & Tang, D. (2022). Artificial neural network-assisted wearable flexible sweat patch for drug management in Parkinson's patients based on vacancy-engineered processing of g-C3N4. *Analytical Chemistry*, *94*(51), 18000-18008. https://doi.org/10.1021/acs.analchem.2c04291

[31] Zhang, S., Suresh, L., Yang, J., Zhang, X., & Tan, S. C. (2022). Augmenting sensor performance with machine learning towards smart wearable sensing electronic systems. *Advanced Intelligent Systems*, *4*(4), 2100194. https://doi.org/10.1002/aisy.202100194

Authors Biography

Dr. Pratyashi Satapathy is an Assistant Professor in the Department of Computer Science and Engineering at Siksha 'O' Anusandhan, Bhubaneswar. Her research areas include artificial intelligence, machine learning, and software development. She has published multiple research papers in international journals and actively mentors students in computing research and innovative IT projects.

Anubhav Bhalla is associated with the Centre of Research Impact and Outcome at Chitkara University, Punjab. His expertise includes institutional research evaluation, academic performance assessment, and innovation management. He contributes to initiatives enhancing research quality, promoting interdisciplinary collaboration, and improving data-driven decision-making in higher education.

Dr.K. Suneetha is a Professor in the Department of Computer Science and Information Technology at JAIN (Deemed-to-be University), Bangalore. Her research interests include software engineering, artificial intelligence, and computer systems optimization. Dr. Suneetha has authored numerous publications and actively mentors students and researchers in advanced computing technologies and IT innovation.

Ananat Marathe is a Professor in the Department of Microbiology at PIMSR, Parul University, Gujarat. His research areas include microbiology, biotechnology, and clinical applications of microbial studies. He is involved in mentoring students, conducting research projects, and publishing scholarly articles that advance knowledge in microbiological sciences and applied research.

Sidhant Das is affiliated with the Chitkara Centre for Research and Development, Chitkara University, Himachal Pradesh. His professional focus includes research evaluation, academic strategy, and institutional development. He actively contributes to enhancing research quality, fostering interdisciplinary collaboration, and promoting innovation-driven projects within higher education institutions.

B.P. Singh is a Professor at the Maharishi School of Engineering & Technology, Maharishi University of Information Technology, Uttar Pradesh. His areas of expertise include computer science, artificial intelligence, and software systems engineering. He has published extensively in peer-reviewed journals and is actively involved in mentoring students, guiding research projects, and contributing to academic development in engineering education.